

Dissipator™ Series Shock Free Wands

The Dissipator™ achieves shock-free performance by combining innovations from the electronics industry with advanced polymer technology. Built up static electric charge is released gradually, creating a safe discharge even for humans and hazardous atmospheres.



Dissipator Basic Pellet Wand

<u>Diameter</u>	<u>Part No.</u>	<u>Length</u>	<u>Price</u>
1-1/2"	GCDT 1501	51"	Call
2"	GCDT 2001	51"	Call
2-1/2"	GCDT 2501	51"	Call
3"	GCDT 3001	51"	Call
4"	GCDT 4001	51"	Call

Benefits:

- Eliminates static shocks; improving employee safety
- Eliminates need for ground wire in hose*; speeds installation; reduces maintenance costs
- Slick and smooth inner surface increases throughput; allows free flow of powder, pellets, flakes or granules
- Durable, high-impact polymer construction withstands abuse
- Lightweight, easy to handle



Dissipator Standard Pellet Wand

With adjustable air register

<u>Diameter</u>	<u>Part No.</u>	<u>Length</u>	<u>Price</u>
1-1/2"	GCDT 1502	51"	Call
2"	GCDT 2002	51"	Call
2-1/2"	GCDT 2502	51"	Call
3"	GCDT 3002	51"	Call
4"	GCDT 4002	51"	Call

* *Ground wire recommended in hazardous areas. Refer to group and class installation guidelines.*



Dissipator Pellet Wand

With fluidizing air channel and adjustable air register

<u>Diameter</u>	<u>Part No.</u>	<u>Length</u>	<u>Price</u>
1-1/2"	GCDT 1503	51"	Call
2"	GCDT 2003	51"	Call
2-1/2"	GCDT 2503	51"	Call
3"	GCDT 3003	51"	Call
4"	GCDT 4003	51"	Call