

MOLD WIRING SYSTEMS

POWERTECH Hot Runner wiring systems and cables eliminate downtime due to mold wiring problems. All terminal blocks are numbered by mold zone, and the mold connectors are pre-wired to the correct terminal block position at the factory. Two standard styles are available, one for DME type systems and one with HBE connectors (commonly used on HUSKY, Mold-Master, Gammaflux, MSI and other). Special configurations are available for any application up to 256 zones. Please call for pricing.

Features and Benefits

- Gets mold up and running faster and keeps it running
- No crimping, no ferrules
- Reduces setup time
- Reduces costly breakdowns
- Simplifies troubleshooting



For DME Type Systems

<u>Model Number</u>	<u>Description</u>	<u>Price</u>
CT-0812	12-zones (10.440 Long x 3.290 wide x 3.125 high)	*
CT-0808	8-zones (10.440 Long x 3.290 wide x 3.125 high)	*
CT-0805	5-zones (10.440 Long x 3.290 wide x 3.125 high)	*
CT-8712-DM	12-zones (7.405 Long x 5.035 wide x 3.125 high)	*
CT-8708-DM	8-zones (7.405 Long x 5.035 wide x 3.125 high)	*
CT-8705-DM	5-zones (7.405 Long x 5.035 wide x 3.125 high)	*
CT-0624-SHD**	24-zones (15.848 Long x 5.015 wide x 3.125 high)	*
CT-0616-SHD**	16-zones (15.848 Long x 5.015 wide x 3.125 high)	*

**These systems are two, 12-zone Systems in one logical compact enclosure. The terminal blocks are wired 1-24

* Please call for current pricing

For HBE Type Systems

<u>Model Number</u>	<u>Description</u>	<u>Price</u>
CT-2206	6-zones (6.360 Long x 3.290 wide x 3.125 high)	*
CT-0412	12-zones (13.870 Long x 3.290 wide x 3.125 high)	*
CT-8712	12-zones (7.405 Long x 5.035 wide x 3.125 high) <i>with 24-pin connector for power and 24-pin connector for thermocouple in two separate housings</i>	*
CT-8712-D	12-zones (7.405 Long x 5.035 wide x 3.125 high) <i>with 24-pin connector for power and 24-pin connector for thermocouple in one housing</i>	*
CT-0624-D**	24-zones (15.848 Long x 5.015 wide x 3.125 high)	*
CT-0616-D**	16-zones (15.848 Long x 5.015 wide x 3.125 high)	*

**These systems are two, 12-zone Systems in one logical compact enclosure. The terminal blocks are wired 1-24

* Please call for current pricing

Web: www.plastixs.com Email: sales@plastixs.com Toll Free: (888) 792.2223
Tel: (508) 842.1606 Fax: (508) 842.4406 151 Memorial Drive, Shrewsbury, MA 01545



POWER & THERMOCOUPLE CABLES

POWERTECH cables are guaranteed to eliminate pin push out in both the cable and mold connector using Powertech Titan Connections. All cables are clearly labeled for Mold End or Controller End and are color coded black for Power and gray for Thermocouple. Cables for stack molds, and special transition and "Y" cables also available.



For DME Type Connectors

Model Number	Cable Type	Description	Price
CT-2512-10	Power	12-zones, 10 foot power cable	*
CT-2508-10	Power	8-zones, 10 foot power cable	*
CT-2505-10	Power	5-zones, 10 foot power cable	*
CT-2512-15	Power	12-zones, 15 foot power cable	*
CT-2508-15	Power	8-zones, 15 foot power cable	*
CT-2505-15	Power	5-zones, 15 foot power cable	*
CT-2512-20	Power	12-zones, 20 foot power cable	*
CT-2508-20	Power	8-zones, 20 foot power cable	*
CT-2505-20	Power	5-zones, 20 foot power cable	*
CT-4512-10	Thermocouple	12-zones, 10 foot thermocouple cable	*
CT-4508-10	Thermocouple	8-zones, 10 foot thermocouple cable	*
CT-4505-10	Thermocouple	5-zones, 10 foot thermocouple cable	*
CT-4512-15	Thermocouple	12-zones, 15 foot thermocouple cable	*
CT-4508-15	Thermocouple	8-zones, 15 foot thermocouple cable	*
CT-4505-15	Thermocouple	5-zones, 15 foot thermocouple cable	*
CT-4512-20	Thermocouple	12-zones, 20 foot thermocouple cable	*
CT-4508-20	Thermocouple	8-zones, 20 foot thermocouple cable	*
CT-4505-20	Thermocouple	5-zones, 20 foot thermocouple cable	*

* Please call for current pricing

For EPIC Type Connectors

Model Number	Cable Type	Description	Price
CT-2412-10	Power	12-zones, 10 foot power cable	*
CT-2424-10	Power	24-zones, 10 foot power cable	*
CT-2412-15	Power	12-zones, 15 foot power cable	*
CT-2424-15	Power	24-zones, 15 foot power cable	*
CT-2412-20	Power	12-zones, 20 foot power cable	*
CT-2424-20	Power	24-zones, 20 foot power cable	*
CT-4412-10	Thermocouple	12-zones, 10 foot thermocouple cable	*
CT-4424-10	Thermocouple	24-zones, 10 foot thermocouple cable	*
CT-4412-15	Thermocouple	12-zones, 15 foot thermocouple cable	*
CT-4424-15	Thermocouple	24-zones, 15 foot thermocouple cable	*
CT-4412-20	Thermocouple	12-zones, 20 foot thermocouple cable	*
CT-4424-20	Thermocouple	24--zones, 20 foot thermocouple cable	*
CT-2606-10	Power/Thermocouple	6-zones, 10 foot combination cable	*
CT-2612-10	Power/Thermocouple	12-zones, 10 foot combination cable	*
CT-2606-15	Power/Thermocouple	6-zones, 15 foot combination cable	*
CT-2612-15	Power/Thermocouple	12-zones, 15 foot combination cable	*
CT-2606-20	Power/Thermocouple	6-zones, 20 foot combination cable	*
CT-2612-20	Power/Thermocouple	12--zones, 20 foot combination cable	*

* Please call for current pricing

Web: www.plastixs.com Email: sales@plastixs.com Toll Free: (888) 792.2223
Tel: (508) 842.1606 Fax: (508) 842.4406 151 Memorial Drive, Shrewsbury, MA 01545

