

# TECHNICAL DATA SHEET



## 48008 Aluminum Anti-Seize

### Product Description

SLIDE® ALUMINUM ANTI-SEIZE COMPOUND is a premium antiseize lubricant containing no lead or copper for maximum resistance to the most corrosive and extreme temperature environments. It has a non-melting synthetic carrier which depolymerizes and dissipates at temperatures exceeding 400°F without leaving a carbon residue.

### Applications

Anti-Seize

### Unit Package Description

8 ounce brush top container

### Generic Description

Aluminum Anti-Seize

### Net Weight Fill

8 net weight ounces

### UPC Code

858799000806

### Units Per Case

1

### Case Weight (lbs)

2

### Appearance

Aluminum Paste

### Flash Point F

>350

### Flash Point C

>176

### Base Type

Petroleum Distillates

### Evaporation Rate

Will not evaporate

### Working Temperature F

32 to 2000 degrees

### Working Temperature C

0 to 1095 degrees

### DOT Proper Shipping Name

Not Regulated

### VOC % (Federal)

2.1

### VOC g/L (Federal)

21

### VOC lbs./Gal (Federal)

0.175

### Removal

Remove with organic or hydrocarbon solvents

### Coefficient of Friction

0.098

### Specific Gravity

1.1

### Penetration ASTM D217-60T

320-350

### Solids Content

21%