

Unique PVC/polyurethane blended core provides excellent resistance to hydrocarbon-based lawn care and pest control chemicals. Reinforced with high tensile strength yarn. PVC ribbed cover provides abrasion resistance.

Construction:

- Tube Black PVC/polyurethane blend.
- Reinforcement High tensile strength yarn.
- Cover Ribbed PVC.

Features:

- Extremely tough and kink resistant.
- PVC/polyurethane blended core provides better chemical resistance than comparable all-PVC hoses.

- Ribbed cover provides excellent abrasion-resistance.
- 300 PSI working pressure.
- Pin-pricked cover vents vapor . . . helps prevent ballooning.
- · Silicone-free.
- One-piece lengths.
- Phthalate Free!

Applications:

- Pest control spraying.
- · Agricultural spraying.
- · Commercial weed spraying.

Service Temperature Range: +15°F (-10°C) to +160°F (+70°C)

Nominal Specifications Approx. Wt. **Max. Working** Standard **Nominal OD Nominal ID Series Size** Pressure† (PSI) per Pkg. Coil Code No. Lengths (In) (mm) (In) (mm) @ 70°F (20°C) @ 122°F (50°C) 300 ft. Coil 400 ft. Coil A1628 06 3/8 9.5 .625 15.9 300 or 400 ft. 36 lbs. 47 lbs. 300 150 A1628 80 1/2 12.7 .770 19.6 300 150 300 or 400 ft. 49 lbs. 65 lbs. A1628 12 3/4 19.1 1.060 26.9 200 100 300 ft. 80 lbs. A1628 16 1 25.4 1.306 33.2 200 100 200 ft. 67 lbs.

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

Note: Use of hydraulic or reusable-type fittings are not recommended for coupling Kuri Tec® hose products. Hose claims involving use of these

fittings will be disallowed.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

PHTHALATE FREE⁽¹⁵⁾

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Distributed By:

