



Antistatic polyurethane hose, heavy duty,
microbe resistant + flame-retardant

Applications

- flexible hose/ ducting for high volume of abrasive powder, bulk material, granulate and for gases
- plastic industry, conveying of granulates and powders: granulate conveying equipment, vacuum hopper/ conveyor, suction conveyor, dosing system, bulk-bag (big bag)-charging and discharging, shredder, mill, extruder, injection moulding machine
- printed circuit board drilling machines (PCB)
- powder spraying, powder coating: e.g. printing industry
- offset printing machine: air supply, air supply cabinet
- industrial vacuum cleaners, vacuum cleaners
- explosion hazard area
- agricultural industry, conveying of seed and fertilizers: seeding machine, seed drill, drilling machine
- agricultural industry: pneumatic grain conveyor
- construction industry, road milling machine
- raw material conveying hose for powders, granulates, sand, quartz, gravel, shards and chips/ shavings
- compressor, side channel blower, vacuum pump, pressure pump, pump
- paper mill, paper and pulp industry, packaging machine: edge strip suctioning system/ edge trim exhaust systems
- surface preparation: shot blasting/ sand blasting recovery (blasting chamber), ship yard, stripping

- machine, flooring preparation machine, grinding machine
- municipal vehicle: sweeper, sweeping machine
- municipal vehicle: lawn mower, slope mower, leaf blower/ leaf collector
- vacuum lifting equipment, vacuum handling system
- silo, silo vehicle/ silo truck, tanker/ tank truck: silo charging, silo discharging
- silo, silo vehicle/ silo truck, tanker/ tank truck: conveying of wood pellets, plastic granulate, plastic powder

Properties

- heavy duty
- highly abrasion resistant
- increased pressure and vacuum resistance
- microbe resistant
- good resistance to oil, gasoline, and chemicals
- very good low temperature flexibility
- flame-retardant according to: UL94-V2
- flame-retardant according to: DIN 4102-B1
- permanently antistatic wall: in accordance with ISO 8031 electrical and surface resistance <math><10^9 \Omega</math> and in accordance with TRGS 727 <math><2,5 * 10^8 \Omega</math>
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: pneumatic transport of flammable dusts and bulk materials (Zone 20, 21, 22 inside), aspiration of combustible dusts (Zone 22 inside), for conveying

- for flammable liquids (inside zone 0, 1, 2), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in zone 0 (gases)
- conforms to the safety regulations of the German Wood Trade Association
- according to DIN 26057 Type 3
- conforms to RoHS guideline
- REACH according to -> Technology / Technical Information / REACH

Temperature range

- 40°F to 195°F
- short time to 255°F

Design, material

- AIRDUC® profile hose
- spring steel wire firmly embedded in the wall
 - wall: permanently antistatic premium ester-polyurethane (Pre-PUR®)
 - wall thickness 0.055 - 0.060 inch approximate

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colors: partially colored, completely colored
- customer-specific branding

I.D. in / mm	O.D. in	Pressure DIN 26057 (50% Elongation) psi	Vacuum DIN 26057 (axially fixed) inHG	Bending Radius in	Weight lbs./ft	Stock length ft	Further production lengths ft	Order No.
standard								
- / 13	0.79	72.50 (145.05)	29.53 (29.53)	0.53	0.095	-	25 50	355-0013-0000
5/8 / 16	0.91	71.05 (130.55)	29.53 (29.53)	0.59	0.110	-	25 50	355-0016-0000
- / 18	1.00	63.90 (120.40)	29.53 (29.53)	5/8	0.115	-	25 50	355-0018-0000
- / 20	1.06	68.45 (120.40)	29.53 (29.53)	0.67	0.155	-	25 50	355-0020-0000
- / 22	1.14	62.80 (119.50)	29.53 (29.53)	0.71	0.170	-	25 50	355-0022-0000
1 / 25	1.25	55.90 (105.95)	29.53 (29.53)	3/4	0.190	25 50	-	355-0025-0000
- / 30	1.57	58.00 (110.15)	29.53 (29.53)	1.00	0.280	-	25 50	355-0030-0000
1.25 / 32	1.65	54.70 (103.65)	29.53 (29.53)	1.02	0.295	25 50	-	355-0032-0000
1.36 / 35	1.75	50.35 (95.20)	29.53 (29.53)	1.08	0.325	-	25 50	355-0035-0000
1.5 / 38	1.89	46.65 (88.05)	29.53 (29.53)	1.14	0.350	25 50	-	355-0038-0000
- / 40	1.97	44.45 (83.85)	29.53 (29.53)	1 1/8	0.365	25 50	-	355-0040-0000
- / 42	2.05	42.15 (80.25)	26.87 (29.53)	1.22	0.375	-	25 50	355-0042-0000
1.75 / 44-45	2.17	39.80 (74.90)	27.02 (29.53)	1.28	0.405	-	25 50	355-0045-0000
2 / 50-51	2.36	36.05 (67.65)	24.36 (29.53)	1.36	0.445	25 50	-	355-0050-0000
- / 55	2.56	32.90 (61.70)	22.15 (29.53)	1.48	0.485	-	25 50	355-0055-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.



I.D.	O.D.	Pressure DIN 26057 (50% Elongation) psi	Vacuum DIN 26057 (axially fixed) inHG	Bending Radius in	Weight lbs./ft	Stock length ft	Further production lengths ft	Order No.
in / mm	in							
2.36 / 60	2.76	30.30 (56.80)	20.23 (29.53)	1.57	0.525	25 50	-	355-0060-0000
2.5 / 63-65	2.95	28.05 (52.50)	18.75 (29.53)	1.67	0.565	25 50	-	355-0065-0000
- / 70	3.19	26.10 (48.90)	15.95 (29.53)	2.44	0.660	25 50	-	355-0070-0000
3 / 75-76	3.39	24.45 (45.70)	14.91 (29.53)	2.58	0.705	25 50	-	355-0075-0000
- / 80	3.58	23.00 (42.85)	14.03 (29.53)	2.72	0.745	-	25 50	355-0080-0000
3.5 / 89-90	3.98	20.50 (38.20)	12.40 (28.06)	3.00	0.840	25 50	-	355-0090-0000
4 / 100-102	4.37	18.50 (34.45)	11.52 (27.46)	3.27	1.000	25 50	-	355-0100-0000
- / 110	4.76	16.80 (31.40)	10.48 (22.74)	3.54	1.095	-	25 50	355-0110-0000
4.5 / 114-115	4.96	16.15 (30.00)	10.04 (20.97)	3.68	1.130	25 50	-	355-0115-0000
4.72 / 120	5.16	15.50 (28.80)	9.60 (19.19)	3.82	1.190	-	25 50	355-0120-0000
5 / 125-127	5.35	14.85 (27.70)	9.30 (17.72)	3.96	1.235	25 50	-	355-0125-0000
- / 130	5.55	14.30 (26.60)	8.86 (16.54)	4.09	1.285	-	25 50	355-0130-0000
5.5 / 140	5.94	13.35 (24.75)	8.27 (14.32)	4.37	1.365	25 50	-	355-0140-0000
6 / 150-152	6.34	12.45 (23.15)	7.97 (15.65)	4.65	1.620	25 50	-	355-0150-0000
6.3 / 160	6.73	11.70 (21.70)	7.53 (13.73)	4.92	1.720	-	25 50	355-0160-0000
- / 170	7.13	11.00 (20.45)	7.09 (12.25)	5.20	1.830	-	25 50	355-0170-0000
- / 175	7.32	10.65 (19.85)	6.79 (11.52)	5.33	1.875	-	25 50	355-0175-0000
7 / 178-180	7.52	10.35 (19.30)	6.64 (10.93)	5.47	1.930	25 50	-	355-0180-0000
8 / 200-203	8.39	9.35 (17.40)	4.43 (10.63)	6.14	2.095	25 50	-	355-0200-0000
- / 225	9.37	8.35 (15.45)	3.84 (8.27)	6.83	2.350	-	25	355-0225-0000
- / 250	10.35	7.55 (13.90)	3.54 (6.50)	7.52	2.605	-	25	355-0250-0000
10 / 254	10.51	7.40 (13.70)	3.40 (6.35)	7.64	2.655	25	-	355-0254-0000
- / 275	11.34	6.80 (12.70)	3.25 (5.32)	8.21	2.860	-	25	355-0275-0000
11 / 280	11.54	6.75 (12.45)	3.10 (5.17)	8.35	2.910	25	-	355-0280-0000
- / 300	12.32	6.30 (11.60)	2.66 (5.76)	8.90	3.465	-	25	355-0300-0000
12 / 305	12.52	6.15 (11.45)	2.66 (5.61)	9.06	3.525	25	-	355-0305-0000
- / 315	12.91	5.95 (11.10)	2.51 (5.17)	9.31	3.635	-	25	355-0315-0000
- / 325	13.31	5.80 (10.75)	2.51 (4.72)	9.59	3.750	-	25	355-0325-0000
13 / 330	13.50	5.75 (10.60)	2.36 (4.58)	9.70	3.810	-	25	355-0330-0000
- / 350	14.29	5.35 (10.00)	2.21 (3.84)	10.28	4.030	-	25	355-0350-0000
- / 400	16.26	4.70 (8.70)	2.07 (3.54)	11.65	5.390	-	25	355-0400-0000
- / 450	18.23	4.20 (7.75)	1.92 (2.66)	13.03	6.050	-	25	355-0450-0000
- / 500	20.24	3.75 (6.95)	1.62 (2.07)	14.45	6.720	-	25	355-0500-0000

neutral imprint: <ID> antistatic + microbe resistant + flame retardant <neutral batch no.> / no cutting

1.25 / 32	1.65	54.70 (103.65)	29.53 (29.53)	1.02	0.295	-	25 50	355-0032-0007
1.5 / 38	1.89	46.65 (88.05)	26.90 (29.53)	1.14	0.350	-	25 50	355-0038-0007
- / 40	1.97	44.45 (83.85)	25.57 (29.53)	1 1/8	0.365	-	25 50	355-0040-0007
1.75 / 44-45	2.17	39.80 (74.90)	22.73 (29.53)	1.28	0.405	-	25 50	355-0045-0007
2 / 50-51	2.36	36.05 (67.65)	20.46 (29.53)	1.36	0.445	-	25 50	355-0050-0007
2.36 / 60	2.76	30.30 (56.80)	17.04 (29.53)	1.57	0.525	-	25 50	355-0060-0007
2.5 / 63-65	2.95	28.06 (52.50)	15.74 (29.53)	1.67	0.565	-	25 50	355-0065-0007
- / 70	3.19	26.10 (48.90)	15.30 (29.53)	2.44	0.660	-	25 50	355-0070-0007
- / 75	3.39	24.45 (45.70)	14.29 (29.53)	2.58	0.705	-	25 50	355-0075-0007
- / 80	3.58	23.00 (42.85)	13.41 (29.53)	2.72	0.745	-	25 50	355-0080-0007
4 / 100-102	4.37	18.50 (34.45)	11.52 (27.46)	3.27	1.000	-	25 50	355-0100-0007
5 / 125-127	5.35	14.85 (27.70)	9.30 (17.72)	3.96	1.235	-	25 50	355-0125-0007
5.5 / 140	5.94	13.35 (24.75)	8.27 (14.32)	4.37	1.365	-	25 50	355-0140-0007
6 / 150-152	6.34	12.45 (23.15)	7.97 (15.65)	4.65	1.620	-	25 50	355-0150-0007
6.3 / 160	6.73	11.70 (21.70)	7.53 (13.73)	4.92	1.720	-	25 50	355-0160-0007

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.



I.D.	O.D.	Pressure DIN 26057 (50% Elongation) psi	Vacuum DIN 26057 (axially fixed) inHG	Bending Radius	Weight	Stock length	Further production lengths	Order No.
in / mm	in			in	lbs./ft	ft	ft	
7 / 178-180	7.52	10.35 (19.30)	6.64 (10.93)	5.47	1.930	-	25 50	355-0180-0007
8 / 200-203	8.39	9.35 (17.40)	4.43 (10.63)	6.14	2.095	-	25 50	355-0200-0007

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only. Additional information at www.norres.com/us/technology-us/

Accessories

					
CLAMP 212	CLAMP 216	CLAMP 212 EC	CLAMP 217	CLAMP 213	CONNECT 228
					
CONNECT SAFETY CLAMP ASSEMBLY 231	CONNECT PRESS ASSEMBLY 232	CONNECT MOULD ASSEMBLY 233	CONNECT THREAD FITTING 234	CONNECT 240 + 241	CONNECT 242
					
CONNECT 243	CONNECT 244	CONNECT 245 VAC- TRUCK	CONNECT 245	CONNECT 246	CONNECT 223
					
CONNECT 270-271	CONNECT STORZ DIN ALU 251	CONNECT TANK TRUCK BRASS 252	CONNECT KAMLOK ALU 253	CONNECT KARDAN 254	

Distributed By: 151 Memorial Drive, Unit H
Shrewsbury, MA 01545
Tel 888.792.2223
sales@plastixs.com



Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.