

High-temperature hose, heavy duty

Applications

- flexible hose/ ducting for high volume of warm abrasive powder, bulk material, granulate and for warm gases
- plastic industry, conveying of granulates and powders: granulate conveying device, vacuum hopper/ conveyor, suction conveyor, dosing system, bulk-bag (big bag)-charging and discharging, shredder, mill, extruder, injection moulding machine
- film blowing machine, cooling air at the extrusion tool
- offset printing machine: air supply, air supply cabinet
- textile industry, steam soaking: steam iron, industrial ironing machine, smoothing iron
- raw material conveying hose for powders, granulates, sand, quartz, gravel, shards and chips/ shavings

- compressor, side channel blower, vacuum pump, pressure pump, pump

Properties

- heavy duty
- highly abrasion resistant
- very good heat resistance (better than comparable TPE and Neoprene)
- increased pressure and vacuum resistance
- good resistance to oil, gasoline, and chemicals
- very good low temperature flexibility
- according to DIN 26057 Type 3
- conforms to RoHS guideline

Temperature range

- 40°F to 255°F
- short time to 300°F

Design, material

AIRDUC® profile hose

- spring steel wire firmly embedded in the wall
- wall: special premium high-temperature polyurethane HT-PUR (Pre-PUR®)
- wall thickness 0.055 - 0.060 inch approx.

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- black (standard)
- customer-specific branding

I.D. in / mm	O.D. in	Pressure DIN 26057 (50% elongation) psi	Vacuum DIN 26057 (axially fixed) inHG	Bending Radius in	Weight lbs./ft	Stock length ft	Further production lengths ft	Order No.
Color black								
1 / 25	1.25	48.95 (-)	28.94 (-)	0.96	0.190	-	25 50	355-0025-1015
1.25 / 32	1.65	47.85 (-)	29.53 (-)	1.25	0.295	-	25 50	355-0032-1015
1.5 / 38	1.89	40.85 (-)	26.87 (-)	1.42	0.350	25 50	-	355-0038-1015
- / 40	1.97	38.95 (-)	25.54 (-)	1.50	0.365	-	25 50	355-0040-1015
2 / 50-51	2.36	31.55 (-)	20.38 (-)	1.73	0.445	25 50	-	355-0050-1015
- / 55	2.56	34.35 (-)	18.75 (-)	1.48	0.485	-	25 50	355-0055-1015
2.36 / 60	2.76	26.55 (-)	16.98 (-)	2.00	0.525	-	25 50	355-0060-1015
2.5 / 63-65	2.95	24.60 (-)	15.65 (-)	2.11	0.565	25 50	-	355-0065-1015
- / 70	3.19	22.85 (-)	13.73 (-)	3.03	0.660	-	25 50	355-0070-1015
3 / 75-76	3.39	21.40 (-)	12.85 (-)	3.17	0.705	25 50	-	355-0075-1015
- / 80	3.58	20.10 (-)	12.11 (-)	3.35	0.745	-	25 50	355-0080-1015
4 / 100-102	4.37	16.15 (-)	10.48 (-)	4.06	1.000	25 50	-	355-0100-1015
5 / 125-127	5.35	13.05 (-)	8.42 (-)	4.90	1.235	25 50	-	355-0125-1015
6 / 150-152	6.34	10.90 (-)	7.68 (-)	5.79	1.620	25 50	-	355-0150-1015
8 / 200-203	8.39	8.20 (-)	3.84 (-)	7.64	2.095	25	-	355-0200-1015
Color transparent								
1.25 / 32	1.65	47.85 (-)	29.53 (-)	1.25	0.295	-	25 50	355-0032-3040
1.5 / 38	1.89	40.85 (-)	26.87 (-)	1.42	0.350	25 50	-	355-0038-3040
- / 40	1.97	38.95 (-)	25.54 (-)	1.50	0.365	-	25 50	355-0040-3040
2 / 50-51	2.36	31.55 (-)	20.38 (-)	1.73	0.445	25 50	-	355-0050-3040
2.36 / 60	2.76	26.55 (-)	16.98 (-)	2.00	0.525	-	25 50	355-0060-3040

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

I.D. in / mm	O.D. in	Pressure DIN 26057 (50% elongation) psi	Vacuum DIN 26057 (axially fixed) inHG	Bending Radius in	Weight lbs./ft	Stock length ft	Further production lengths ft	Order No.
2.5 / 63-65	2.95	24.60 (-)	15.65 (-)	2.11	0.565	25 50	-	355-0065-3040
- / 70	3.19	22.85 (-)	13.73 (-)	3.03	0.660	-	25 50	355-0070-3040
- / 80	3.58	20.10 (-)	12.11 (-)	3.35	0.745	-	25 50	355-0080-3040
4 / 100-102	4.37	16.15 (-)	10.48 (-)	4.06	1.000	25 50	-	355-0100-3040

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only. Additional information at www.norres.com/us/technology-us/

Accessories



CLAMP 212



CLAMP 216




CLAMP 212 EC



CLAMP 217



CLAMP 213



CONNECT 228

CONNECT SAFETY
CLAMP ASSEMBLY 231CONNECT PRESS
ASSEMBLY 232CONNECT MOULD
ASSEMBLY 233CONNECT THREAD
FITTING 234

CONNECT 270-271

Distributed By:

151 Memorial Drive, Unit H
Shrewsbury, MA 01545
Tel 888.792.2223
sales@plastixs.com

plastixs®
manufacturing solutions

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.