



FREEZEPRO® VALVE INSULATION JACKETS PRODUCT SPECS

Each FreezePro® Valve part number has its own individual **Length, Width, Weight, Circumference, Watts, Amps** and **Heating Cable Length** dimensions. All additional product information stays the same. Use the table below to help you indentify the **Length (A), Width (B), Weight (C), Circumference (D), Watts (E), Amps (F)** and **Heating Cable Length (G)** for each individual FreezePro® part number. Fill in the designated sections **(A, B, C, D, E, F and G)** to get your product spec descriptions for each FreezePro® Valve part number.

PRODUCT DESCRIPTION

ITEM	Frost Protection Insulation	FASTENING SYSTEM	Lacing Anchor, S.S. Wire
LENGTH	(A)	APPROX. "R" FACTOR	.48
WIDTH	(B)	TEMPERATURE RANGE	-40°F / -40°C to 200°F / 93°C
THICKNESS	3in / 76mm	COLOR	Gray / Grey
INSULATION MATERIAL	Mineral Wool	WEIGHT	(C)
JACKET MATERIAL	Silicone	FIT	Universal
DIAMETER RANGE	N/A	CIRCUMFERENCE RANGE	(D)
WATTS	(E)	AMPS	(F)
VOLTAGE	120	POWER CORD TYPE	(18 AWG) 3-Prong Grounded Plug
HEATING CABLE LENGTH	(G)	COLD LEAD LENGTH	98in / 2489mm



FOR EXAMPLE

FPV 1206

ITEM	Frost Protection Insulation	FASTENING SYSTEM	Lacing Anchor, S.S. Wire
LENGTH	12in / 305mm	APPROX. "R" FACTOR	.48
WIDTH	6in / 152mm	TEMPERATURE RANGE	-40°F / -40°C to 200°F / 93°C
THICKNESS	3in / 76mm	COLOR	Gray / Grey
INSULATION MATERIAL	Mineral Wool	WEIGHT	1lbs. / 0.45kg
JACKET MATERIAL	Silicone	FIT	Universal
DIAMETER RANGE	N/A	CIRCUMFERENCE RANGE	0in-7in / 0mm-178mm
WATTS	90	AMPS	0.75
VOLTAGE	120	POWER CORD TYPE	(18 AWG) 3-Prong Grounded Plug
HEATING CABLE LENGTH	120in / 3048mm	COLD LEAD LENGTH	98in / 2489mm



Part #	(A)	(B)	(C)	(D)	(E)	(F)	(G)
FPV1206	12" (305mm)	6" (152mm)	1.0lbs. (0.45kg)	0" - 7" (0mm - 178mm)	90	0.75	120" (3048mm)
FPV1212	12" (305mm)	12" (305mm)	2.0lbs. (0.91kg)	0" - 7" (0mm - 178mm)	90	0.75	120" (3048mm)
FPV1218	12" (305mm)	18" (457mm)	2.0lbs. (0.91kg)	0" - 7" (0mm - 178mm)	90	0.75	120" (3048mm)
FPV1224	12" (305mm)	24" (610mm)	2.0lbs. (0.91kg)	0" - 7" (0mm - 178mm)	90	0.75	120" (3048mm)
FPV1806	18" (457mm)	6" (152mm)	1.0lbs. (0.45kg)	7" - 13" (178mm - 330mm)	90	0.75	120" (3048mm)
FPV1812	18" (457mm)	12" (305mm)	2.0lbs. (0.91kg)	7" - 13" (178mm - 330mm)	90	0.75	120" (3048mm)
FPV1818	18" (457mm)	18" (457mm)	3.0lbs. (1.36kg)	7" - 13" (178mm - 330mm)	90	0.75	120" (3048mm)
FPV1824	18" (457mm)	24" (610mm)	4.0lbs. (1.81kg)	7" - 13" (178mm - 330mm)	90	0.75	120" (3048mm)
FPV2406	24" (610mm)	6" (152mm)	1.25lbs. (0.57kg)	13" - 19" (330mm - 483mm)	90	0.75	120" (3048mm)
FPV2412	24" (610mm)	12" (305mm)	2.25lbs. (0.45kg)	13" - 19" (330mm - 483mm)	90	0.75	120" (3048mm)
FPV2418	24" (610mm)	18" (457mm)	3.25lbs. (1.48kg)	13" - 19" (330mm - 483mm)	90	0.75	120" (3048mm)
FPV2424	24" (610mm)	24" (610mm)	4.25lbs. (1.93kg)	13" - 19" (330mm - 483mm)	180	1.5	240" (6096mm)
FPV3006	30" (762mm)	6" (152mm)	2.0lbs. (0.91kg)	19" - 25" (483mm - 635mm)	90	0.75	120" (3048mm)
FPV3012	30" (762mm)	12" (305mm)	3.0lbs. (1.36kg)	19" - 25" (483mm - 635mm)	90	0.75	120" (3048mm)
FPV3018	30" (762mm)	18" (457mm)	4.0lbs. (1.81kg)	19" - 25" (483mm - 635mm)	180	1.5	240" (6096mm)
FPV3024	30" (762mm)	24" (610mm)	6.0lbs. (2.72kg)	19" - 25" (483mm - 635mm)	180	1.5	240" (6096mm)
FPV3606	36" (914mm)	6" (152mm)	1.75lbs. (0.79kg)	25" - 31" (635mm - 787mm)	90	0.75	120" (3048mm)
FPV3612	36" (914mm)	12" (305mm)	3.25lbs. (1.47kg)	25" - 31" (635mm - 787mm)	90	0.75	120" (3048mm)
FPV3618	36" (914mm)	18" (457mm)	4.5lbs. (2.04kg)	25" - 31" (635mm - 787mm)	180	1.5	240" (6096mm)
FPV3624	36" (914mm)	24" (610mm)	6.25lbs. (2.83kg)	25" - 31" (635mm - 787mm)	180	1.5	240" (6096mm)
FPV4206	42" (1067mm)	6" (152mm)	2.0lbs. (0.91kg)	31" - 37" (787mm - 940mm)	90	0.75	120" (3048mm)



Part #	(A)	(B)	(C)	(D)	(E)	(F)	(G)
FPV4212	42" (1067mm)	12" (305mm)	4.0lbs. (1.81kg)	31" - 37" (787mm - 940mm)	90	0.75	120" (3048mm)
FPV4218	42" (1067mm)	18" (457mm)	6.0lbs. (2.72kg)	31" - 37" (787mm - 940mm)	180	1.5	240" (6096mm)
FPV4224	42" (1067mm)	24" (610mm)	8.0lbs. (3.63kg)	31" - 37" (787mm - 940mm)	180	1.5	240" (6096mm)
FPV4806	48" (1219mm)	6" (152mm)	2.25lbs. (1.02kg)	37" - 42" (940mm - 1067mm)	180	1.5	240" (6096mm)
FPV4812	48" (1219mm)	12" (305mm)	4.25lbs. (1.93kg)	37" - 42" (940mm - 1067mm)	180	1.5	240" (6096mm)
FPV4818	48" (1219mm)	18" (457mm)	6.25lbs. (2.83kg)	37" - 42" (940mm - 1067mm)	180	1.5	240" (6096mm)
FPV4824	48" (1219mm)	24" (610mm)	8.25lbs. (3.74kg)	37" - 42" (940mm - 1067mm)	180	1.5	240" (6096mm)
FPV5406	54" (1372mm)	6" (152mm)	2.5lbs. (1.13kg)	42" - 49" (1067mm - 1245mm)	180	1.5	240" (6096mm)
FPV5412	54" (1372mm)	12" (305mm)	4.75lbs. (2.15kg)	42" - 49" (1067mm - 1245mm)	180	1.5	240" (6096mm)
FPV5418	54" (1372mm)	18" (457mm)	7.25lbs. (3.29kg)	42" - 49" (1067mm - 1245mm)	180	1.5	240" (6096mm)
FPV5424	54" (1372mm)	24" (610mm)	9.25lbs. (4.2kg)	42" - 49" (1067mm - 1245mm)	180	1.5	240" (6096mm)
FPV6006	60" (1524mm)	6" (152mm)	2.75lbs. (1.25kg)	49" - 55" (1245mm - 1397mm)	180	1.5	240" (6096mm)
FPV6012	60" (1524mm)	12" (305mm)	5.25lbs. (2.83kg)	49" - 55" (1245mm - 1397mm)	180	1.5	240" (6096mm)
FPV6018	60" (1524mm)	18" (457mm)	8.25lbs. (3.74kg)	49" - 55" (1245mm - 1397mm)	180	1.5	240" (6096mm)
FPV6024	60" (1524mm)	24" (610mm)	10.25lbs. (4.65kg)	49" - 55" (1245mm - 1397mm)	180	1.5	240" (6096mm)