



FREEZEPRO® WRAP INSULATION JACKETS PRODUCT SPECS

Each FreezePro® Wrap part number has its own individual **Length, Width, Weight, Diameter, Circumference, Watts, Amps** and **Heating Cable Length** dimensions. All additional product information stays the same. Use the table below to help you identify the **Length (A), Width (B), Weight (C), Diameter (D), Circumference (E), Watts (F), Amps (G)** and **Heating Cable Length (H)** for each individual FreezePro® part number. Fill in the designated sections **(A, B, C, D, E, F, G and H)** to get your product spec descriptions for each FreezePro® Wrap part number.

PRODUCT DESCRIPTION

ITEM	Frost Protection Insulation	FASTENING SYSTEM	Lacing Anchor, S.S. Wire
LENGTH	(A)	APPROX. "R" FACTOR	.48
WIDTH	(B)	TEMPERATURE RANGE	-40°F / -40°C to 200°F / 93°C
THICKNESS	3in / 76mm	COLOR	Gray / Grey
INSULATION MATERIAL	Mineral Wool	WEIGHT	(C)
JACKET MATERIAL	Silicone	FIT	Universal
DIAMETER RANGE	(D)	CIRCUMFERENCE RANGE	(E)
WATTS	(F)	AMPS	(G)
VOLTAGE	120	POWER CORD TYPE	(18 AWG) 3-Prong Grounded Plug
HEATING CABLE LENGTH	(H)	COLD LEAD LENGTH	98in / 2489mm



FOR EXAMPLE

FPW 1206

ITEM	Frost Protection Insulation	FASTENING SYSTEM	Lacing Anchor, S.S. Wire
LENGTH	12in / 305mm	APPROX. "R" FACTOR	.48
WIDTH	6in / 152mm	TEMPERATURE RANGE	-40°F / -40°C to 200°F / 93°C
THICKNESS	3in / 76mm	COLOR	Gray / Grey
INSULATION MATERIAL	Mineral Wool	WEIGHT	1lbs. / 0.45kg
JACKET MATERIAL	Silicone	FIT	Universal
DIAMETER RANGE	0in-2in / 0mm-51mm	CIRCUMFERENCE RANGE	0in-6in / 0mm-152mm
WATTS	90	AMPS	0.75
VOLTAGE	120	POWER CORD TYPE	(18 AWG) 3-Prong Grounded Plug
HEATING CABLE LENGTH	120in / 3048mm	COLD LEAD LENGTH	98in / 2489mm



Part #	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)
FPW1206	12" (305mm)	6" (152mm)	1.0lbs. (0.45kg)	0" - 2" (0 - 60mm)	0" - 6" (0 - 152mm)	90	0.75	120" (3048mm)
FPW1212	12" (305mm)	12" (305mm)	2.0lbs. (0.91kg)	0" - 2" (0 - 60mm)	0" - 6" (0 - 152mm)	90	0.75	120" (3048mm)
FPW1218	12" (305mm)	18" (457mm)	2.0lbs. (0.91kg)	0" - 2" (0 - 60mm)	0" - 6" (0 - 152mm)	90	0.75	120" (3048mm)
FPW1224	12" (305mm)	24" (610mm)	2.0lbs. (0.91kg)	0" - 2" (0 - 60mm)	0" - 6" (0 - 152mm)	90	0.75	120" (3048mm)
FPW1806	18" (457mm)	6" (152mm)	1.0lbs. (0.45kg)	2" - 4" (60 - 102mm)	6" - 13" (152 - 330mm)	90	0.75	120" (3048mm)
FPW1812	18" (457mm)	12" (305mm)	2.0lbs. (0.91kg)	2" - 4" (60 - 102mm)	6" - 13" (152 - 330mm)	90	0.75	120" (3048mm)
FPW1818	18" (457mm)	18" (457mm)	3.0lbs. (1.36kg)	2" - 4" (60 - 102mm)	6" - 13" (152 - 330mm)	90	0.75	120" (3048mm)
FPW1824	18" (457mm)	24" (610mm)	4.0lbs. (1.81kg)	2" - 4" (60 - 102mm)	6" - 13" (152 - 330mm)	90	0.75	120" (3048mm)
FPW2406	24" (610mm)	6" (152mm)	1.25lbs. (0.57kg)	4" - 6" (102 - 152mm)	13" - 19" (330 - 483mm)	90	0.75	120" (3048mm)
FPW2412	24" (610mm)	12" (305mm)	2.25lbs. (0.45kg)	4" - 6" (102 - 152mm)	13" - 19" (330 - 483mm)	90	0.75	120" (3048mm)
FPW2418	24" (610mm)	18" (457mm)	3.25lbs. (1.48kg)	4" - 6" (102 - 152mm)	13" - 19" (330 - 483mm)	90	0.75	120" (3048mm)
FPW2424	24" (610mm)	24" (610mm)	4.25lbs. (1.93kg)	4" - 6" (102 - 152mm)	13" - 19" (330 - 483mm)	180	1.5	240" (6096mm)
FPW3006	30" (762mm)	6" (152mm)	2.0lbs. (0.91kg)	6" - 8" (152 - 203mm)	19" - 25" (483 - 635mm)	90	0.75	120" (3048mm)
FPW3012	30" (762mm)	12" (305mm)	3.0lbs. (1.36kg)	6" - 8" (152 - 203mm)	19" - 25" (483 - 635mm)	90	0.75	120" (3048mm)
FPW3018	30" (762mm)	18" (457mm)	4.0lbs. (1.81kg)	6" - 8" (152 - 203mm)	19" - 25" (483 - 635mm)	180	1.5	240" (6096mm)
FPW3024	30" (762mm)	24" (610mm)	6.0lbs. (2.72kg)	6" - 8" (152 - 203mm)	19" - 25" (483 - 635mm)	180	1.5	240" (6096mm)
FPW3606	36" (914mm)	6" (152mm)	1.75lbs. (0.79kg)	8" - 10" (203 - 254mm)	25" - 31" (635 - 787mm)	90	0.75	120" (3048mm)
FPW3612	36" (914mm)	12" (305mm)	3.25lbs. (1.47kg)	8" - 10" (203 - 254mm)	25" - 31" (635 - 787mm)	90	0.75	120" (3048mm)
FPW3618	36" (914mm)	18" (457mm)	4.5lbs. (2.04kg)	8" - 10" (203 - 254mm)	25" - 31" (635 - 787mm)	180	1.5	240" (6096mm)
FPW3624	36" (914mm)	24" (610mm)	6.25lbs. (2.83kg)	8" - 10" (203 - 254mm)	25" - 31" (635 - 787mm)	180	1.5	240" (6096mm)
FPW4206	42" (1067mm)	6" (152mm)	2.0lbs. (0.91kg)	10" - 12" (254 - 305mm)	31" - 38" (787 - 965mm)	90	0.75	120" (3048mm)



Part #	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)
FPW4212	42" (1067mm)	12" (305mm)	4.0lbs. (1.81kg)	10" - 12" (254 - 305mm)	31" - 38" (787 - 965mm)	90	0.75	120" (3048mm)
FPW4218	42" (1067mm)	18" (457mm)	6.0lbs. (2.72kg)	10" - 12" (254 - 305mm)	31" - 38" (787 - 965mm)	180	1.5	240" (6096mm)
FPW4224	42" (1067mm)	24" (610mm)	8.0lbs. (3.63kg)	10" - 12" (254 - 305mm)	31" - 38" (787 - 965mm)	180	1.5	240" (6096mm)
FPW4806	48" (1219mm)	6" (152mm)	2.25lbs. (1.02kg)	12" - 14" (305 - 356mm)	38" - 44" (965 - 1118mm)	180	1.5	240" (6096mm)
FPW4812	48" (1219mm)	12" (305mm)	4.25lbs. (1.93kg)	12" - 14" (305 - 356mm)	38" - 44" (965 - 1118mm)	180	1.5	240" (6096mm)
FPW4818	48" (1219mm)	18" (457mm)	6.25lbs. (2.83kg)	12" - 14" (305 - 356mm)	38" - 44" (965 - 1118mm)	180	1.5	240" (6096mm)
FPW4824	48" (1219mm)	24" (610mm)	8.25lbs. (3.74kg)	12" - 14" (305 - 356mm)	38" - 44" (965 - 1118mm)	180	1.5	240" (6096mm)
FPW6006	60" (1524mm)	6" (152mm)	2.75lbs. (1.25kg)	14" - 17" (356 - 432mm)	44" - 53" (1118 - 1346mm)	180	1.5	240" (6096mm)
FPW6012	60" (1524mm)	12" (305mm)	5.25lbs. (2.83kg)	14" - 17" (356 - 432mm)	44" - 53" (1118 - 1346mm)	180	1.5	240" (6096mm)
FPW6018	60" (1524mm)	18" (457mm)	8.25lbs. (3.74kg)	14" - 17" (356 - 432mm)	44" - 53" (1118 - 1346mm)	180	1.5	240" (6096mm)
FPW6024	60" (1524mm)	24" (610mm)	10.25lbs. (4.65kg)	14" - 17" (356 - 432mm)	44" - 53" (1118 - 1346mm)	180	1.5	240" (6096mm)