

Full Flow Swivel Coupling

Ribbed interior screws over outside of the hose.



Popular in mulch, bark, wood chip and other lawn surfacing applications.



Swivel joint reduces instances of hose twisting.



Aluminum Full-Flow Swivel Coupling Set (NPSM Threads)

Part Number	Size (in)	Weight Each (lbs)	Std. Carton
AL-MHS400	4	2.67	1

Fits the following Tigerflex™ series hoses:

- MULCH™
- MULCH-LT™
- BARK™
- LK™
- UV1™

Features and Advantages:

- **Full Flow Interior** – Prevents material build-up due to the absence of an interior hose shank. Instead, our coupling screws easily and securely over the outside of the hose to provide full flow.
- **Swivel Joint** – Stainless steel ball bearings ensure smooth swivel action, reducing instances of hose twisting.
- **Versatile 2-piece Design** – Coupling consists of male and female ends connected by NPSM threads. Male portion also sold separately.

Male portion also sold separately, connects to female thread (NPSM) quick acting couplings.



Aluminum Full-Flow Swivel Coupling Male (NPSM Threads)

Part Number	Size (in)	Weight Each (lbs)	Std. Carton
AL-MHM400	4	0.93	1



Aluminum Part D Coupler X Female (NPSM Threads)

Part Number	Size (in)	Weight Each (lbs)	Std. Carton
AL-MHD400	4	2.16	1



Aluminum Part A Male Adapter X Female (NPSM Threads)

Part Number	Size (in)	Weight Each (lbs)	Std. Carton
AL-MHA400	4	1.58	1

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.