Kuri Tec[®]

HS1171, HS1174, HS1176 Series

General Service PVC Pneumatic Air Tool Hose Assemblies



Service Temperature Range: -15°F (-26°C) to +150°F (+65°C)

Nominal Specifications													
Standard Stock Colors			Size	Nominal ID		Nominal OD		Maximum Working Pressure† (PSI)		Assembled	Approx. Wt. per Pkg.		
HS1171 Yellow	HS1174 Red	HS1176 Blue	Code	(ln)	(mm)	(ln)	(mm)	@70°F (20°C)	@122°F (50°C)	Lengths	25 ft.	50 ft.	100 ft.
V	V	V	04	1/4	6.5	.475	12.1	300	150	25/50/100 ft.	1.9 lbs.	3.7 lbs.	7.4 lbs.
V	V	/	06	3/8	9.5	.600	15.2	300	150	25/50/100 ft.	2.6 lbs.	5.1 lbs.	10.2 lbs.
V	V	V	08	1/2	12.7	.750	19.1	300	150	25/50/100 ft.	3.5 lbs.	7.0 lbs.	14.0 lbs

Note: Hose assemblies are furnished with the following fittings: 1/4" ID - 1/4" X 1/4" M NPT, 3/8" ID - 3/8" X 1/4" M NPT, 1/2" ID - 1/2" X 3/8" M NPT.

HS1181, HS1184, HS1186 Series

Utility-Grade PVC Air Tool Hose Assemblies



Service Temperature Range: +14°F (-10°C) to +150°F (+65°C)

Nominal Specifications												
Standard Stock Colors		Size	Nominal ID		Nominal OD		Maximum Working Pressure† (PSI)	Assembled	Approx. Wt. per Pkg.			
HS1181 Yellow		HS1186 Blue		(ln)	(mm)	(In)	(mm)	@70°F (20°C)	Lengths	25 ft.	50 ft.	100 ft.
<<	77	>>	04 06	1/4 3/8	6.5 9.5	.475 .600	12.1 15.2	300 300	25/50/100 ft. 25/50/100 ft.	1.9 lbs. 2.6 lbs.		

Note: Hose assemblies are furnished with the following fittings: 1/4" ID - 1/4" X 1/4"M NPT, 3/8" ID - 3/8" X 1/4"M NPT.

 $\begin{tabular}{ll} \begin{tabular}{ll} \beg$

Note: Refer to page 34 for Technical Information. **NOTE:** For details of the following compliances mentioned above, refer to footnotes listed on page 63.

PHTHALATE FREE⁽¹⁵⁾

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Distributed By:



[†] **Note:** Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures. **Note:** Refer to page 33 for Technical Information.