# Kuri Tec<sup>®</sup>

## PNEU-THANE<sup>™</sup> HS5090, HS5094, HS5096 Series



T U N D R A 👧 A I R

Kuri Teo

HS1236-06X25

VENIOLOUNINI VENIOLUNINI

Lightweight Reinforced Polyurethane Pneumatic Air Tool Hose Assemblies (with Rubber Bend Restrictors)

Service Temperature Range: -40°F (-40°C) to +185°F (+85°C)

Nom	inal Speci	ficat	ions									
Standard Stock Colors		Size	Nominal ID		Nominal OD		Maximum Working Pressure† (PSI)		Assembled	Approx. Wt. per Pkg <sub>l</sub>		
HS5090 Aqua	HS5094 Red HS5096 Blue	Code	(In)	(mm)	(In)	(mm)	@70°F (20°C)	@122°F (50°C)	Lengths	25 ft.	50 ft.	100 ft.
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	~ ~	04 06	1/4 3/8	6.5 9.5	.395 .560	10.0 14.2	250 250	200 200	25/50/100 ft. 25/50/100 ft.	1 lbs. 1.5 lbs.	2 lbs. 3 lbs.	4 lbs. 6 lbs.

Note: Hose assemblies are furnished with the following fittings: 1/4" ID - 1/4" X 1/4"M NPT, 3/8" ID - 3/8" X 1/4"M NPT.

Note: Refer to page 28 for Technical Information.

## TUNDRA-AIR® HS1231, HS1234, HS1236 Series

### High Grade Low Temperature Air Hose Assemblies

(with Rubber Bend Restrictors)

1/4" and 3/8" sizes only.

Service Temperature Range: -65°F (-54°C) to +150°F (+65°C)

Phthalate

#### Nominal Specifications

		_											
Standard Stock Colors			Size	Size Nominal ID		Nominal OD		Maximum Working Pressure† (PSI)		Assembled	Approx. Wt. per Pkg.		
HS1231 Yellow	HS1234 Red	HS1236 Blue	Code	(In)	(mm)	(In)	(mm)	@70°F (20°C)	@122°F (50°C)	Lengths	25 ft.	50 ft.	100 ft.
~	~	~	04	1/4	6.5	.500	12.7	300	160	25/50/100 ft.	2.0 lbs.	4.0 lbs.	7.8 lbs.
~	~	~	06	3/8	9.5	.625	15.9	300	160	25/50/100 ft.	2.8 lbs.	5.5 lbs.	10.7 lbs.
~	~	~	08	1/2	12.7	.781	19.8	300	160	25/50/100 ft.	4.1 lbs.	8.1 lbs.	16.0 lbs.

**† Note:** Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures. **Note:** Hose assemblies are furnished with the following fittings: 1/4" ID – 1/4" X 1/4"M NPT, 3/8" ID – 3/8" X 1/4"M NPT, 1/2" ID – 1/2" X 3/8"M NPT. **Note:** Refer to page 30 for Technical Information.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

### Phthalate Free<sup>(15)</sup>

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Distributed By:

151 Memorial Drive, Unit H Shrewsbury, MA 01545 Tel 888.792.2223 sales@plastixs.com



REVISED

ATURE