

Kuri Tec[®]

K1154, K1156 Series General Purpose PVC Air & Water Hose

A general purpose PVC air and water hose for in plant and outdoor applications in temperate climate conditions.

Construction:

- Tube Black PVC compound.
- Reinforcement High tensile strength yarn.
- Cover PVC compound, available in two colors: K1154 – Red and K1156 – Blue.

Features:

- Economical, flexible and lightweight.
- Excellent abrasion resistance.
- U. V. and weather resistant.
- Non-marking pin-pricked cover.

- Silicone-free materials.
- Complies with RMA's Class B designation for medium/ high oil resistance.
- One piece lengths.
- Phthalate Free!

Applications:

- Transfer of air, water and mild water soluble chemicals.
- Ideal for in-plant applications that require an economical general purpose hose.
- Excellent air supply line for pneumatic tools and paint spray systems.

Nominal Specifications												
Series No.		Size	Nominal ID		Nominal OD		Max. Working Pressure† (PSI)		Standard Length		Approx. Wt. per Pkg.	
K1154 Red	K1156 Blue	Code	(In)	(mm)	(In)	(mm)	@70°F (20°C)	@122°F (50°C)	Reel	Coil	Reel	Coil
~	 ✓ 	04	1/4	6.4	.500	12.7	300	150	500 ft.	100 ft.	44 lbs.	8 lbs.
~	*	05	5/16	7.9	.625	15.9	300	150	500 ft.	100 ft.	68 lbs.	13 lbs.
~	 ✓ 	06	3/8	9.5	.625	15.9	300	150	500 ft.	100 ft.	56 lbs.	11 lbs.
~	 ✓ 	08	1/2	12.7	.750	19.1	300	150	500 ft.	100 ft.	70 lbs.	14 lbs.
~	 ✓ 	10	5/8	15.9	.895	22.6	200	100	300 ft.	100 ft.	60 lbs.	18 lbs.
~	 ✓ 	12	3/4	19.1	1.030	26.2	200	75	300 ft.	100 ft.	72 lbs.	22 lbs.
~	~	16	1	25.4	1.313	33.3	150	75	300 ft.	100 ft.	105 lbs.	31 lbs.

Service Temperature Range: +14°F (-10°C) to +150°F (+65°C)

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

★ Note: Series K1156 5/16" ID size is a non stock item.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

Phthalate Free⁽¹⁵⁾

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

plastiXs

nanufacturing solutions

Distributed By:

151 Memorial Drive, Unit H Shrewsbury, MA 01545 Tel 888.792.2223 sales@plastixs.com