

Kuri Tec[®]

NAUTILUS™ K2W Series Weighted Aeration Tubing

A special weighted flexible PVC tubing that is ideal for trouble free delivery of air to pond aeration systems.

Construction:

Special black weighted PVC compound ensures durability, reliability and sink-ability while in use.

Features:

- Remains flexible for use in a wide range of temperatures.
- Greatly reduces installation time, requires no maintenance following instructions.
- Naturally sinks without the use of additional weights or anchors.
- Available in 3/8", 1/2", 5/8, 3/4 and 1" ID sizes to fit most aeration systems.

- Packaged in coils or reels depending on application lengths required.
- Phthalate Free!

Applications:

- Pond and lake aeration.
- Water recirculation.
- Ice clearing.
- Wastewater lagoons.
- · Commercial hatcheries.

Service Temperature Range: 25°F (-4°C) to +150°F (+65°C)

Nominal Specifications

and the second									
	Series No.	Size Code	Nominal ID		Nominal OD		Working Pressure†	Standard Length	Approx. Wt.
			(ln)	(mm)	(In)	(mm)	(PSI) @ 70°F (20°C)	Coils	lbs/Pkg.
	K2W	0611	3/8"	9.5	0.690	17.5	50	300 ft.	60 lbs.
	K2W	0815	1/2"	12.7	0.960	24.4	50	200 ft.	80 lbs.
	K2W	1017	5/8"	15.9	1.065	27.1	50	100 ft.	44 lbs.
	K2W	1220	3/4"	19.1	1.275	32.4	40	100 ft.	63 lbs.
	K2W	1627	1"	25.4	1.690	42.9	40	100 ft.	111 lbs.

Note: The Nautilus Weighted Aeration Tubing ID sizes and specification information listed above are based on average dimensions. Special ID sizes and lengths are available on request. All products are priced on request. Check with your local sales office for additional details.

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

PHTHALATE FREE⁽¹⁵⁾, RoHS⁽¹⁶⁾

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Distributed By:

