



NEW
LENGTHS



King Bee™

KBEE™ Series

Polyethylene Liquid Suction and Wastewater Hose



General Applications:

- Pumps, rental and construction dewatering
- Pumps, trash
- Septic and wastewater handling
- Water suction – standard duty

Construction: Flexible polyethylene (LDPE) tube with polyethylene (LDPE) ribs and cuffed ends.

Service Temperature: -40°F (-40°C) to 150°F (+65°C)*

Features and Advantages:

- **Superior Flexibility!** – Corrugated tube and ribs provides high flexibility, perfect for maneuvering in tight areas such as portable toilets.
- **“Cold-Flex” Materials** – Hose remains flexible in sub-zero temperatures.
- **Crush Resistant** – Will spring back to original shape after being crushed, will not kink!
- **Easy Slide Helix** – Exposed ribs protect hose tube from cover wear, and allow hose to slide easily over rough surfaces. Easy-to-handle.



- **Leak Proof Cuffs** – Overmolded cuffs eliminate leaking and will not separate from the hose. Each cuff and unit is 100% factory tested.
- **Additional 2" Cuffs** – Additional 2" cuffs are available for making hose repairs and custom lengths.

King Bee Additional Cuff

Part Number	ID (in.)	Weight (lbs.)
CUFF2	2	0.2



Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Working Pressure (psi @ 68°F)	Vacuum Rating (in. Hg @ 68°F)	Min. Bending Radius (in. @ 68°F)	Standard Length (ft.)	Weight (lbs./ft.)
KBEE200	2	52.7	2.76	69.5	15	29	3.5	60/50/40/30/25/20/10	0.72
KBEE300	3	76.0	4.06	97.0	7	29	6.5	60/50/30/25/20	1.36

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

*Actual service temperature range is application dependent.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

Distributed By: 151 Memorial Drive, Unit H
Shrewsbury, MA 01545
Tel 888.792.2223
sales@plastixs.com

plastixs®
manufacturing solutions

KKBBR0718