















PVC Ducting/Material Handling Hose

General Applications:

- Dust collection
- Lawn and leaf collection
- Material handling light duty

Construction: PVC tube with rigid PVC helix.

Service Temperature Range:

-20°F (-29°C) to +150°F (+65°C)*





Features and Advantages:

- "Cold-Flex" Materials Hose remains flexible in sub-zero temperatures.
- Transparent Construction (LKC series only) "See-the-flow." Allows for visual confirmation of material flow.
- Easy Slide Helix Rigid helix design protects hose tube from cover wear, and allows hose to slide easily over rough surfaces. Easy-to-handle.
- Phthalate Free

Nominal Specifications												
	Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius	Standard	Woight
		(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F	at 68°F (in)	Length (ft)	Weight (lbs/ft)
	LK/LKC400	4	101.6	4.57	114.8	8	4	13	7	3	100/50	0.85
	LKC500	5	128.0	5.55	141.0	7	3	10	6	5	100	0.93
	LK/LKC600	6	152.4	6.63	168.3	6	3	7	5	6	100/50	1.34
	LKC700	7	177.8	7.56	192.0	4	2	6	4	7	50	1.53
	LK/LKC800	8	203.2	8.63	219.3	4	2	5	3	8	50/25	2.00

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

NOTE: For details of the following compliances, refer to footnotes listed on page 63.

*Actual service temperature range is application dependent.