

RECHNER SENSORS

North American Made Capacitive Sensors - NORMLINE SERIES

M18 DC



NPN:
KAS-70-A13-A-K-Y3-NL

PNP:
KAS-80-A13-A-K-Y3-NL

- Flush
- $S_d=1.....8$ mm
- M12 Connector
- M18 x 1 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 12.....30 VDC

M18 DC



NPN:
KAS-70-A23-A-K-Y3-NL

PNP:
KAS-80-A23-A-K-Y3-NL

- Non-Flush
- $S_d=1.....10$ mm
- M12 Connector
- M18 x 1 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 12.....30 VDC

M30 DC



NPN:
KAS-70-A14-A-K-Y3-NL

PNP:
KAS-80-A14-A-K-Y3-NL

- Flush
- $S_d=2.....20$ mm
- M12 Connector
- M30 x 1.5 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 12.....30 VDC

M30 DC



NPN:
KAS-70-A24-A-K-Y3-NL

PNP:
KAS-80-A24-A-K-Y3-NL

- Non-Flush
- $S_d=2.....25$ mm
- M12 Connector
- M30 x 1.5 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 12.....30 VDC



M32 DC



NPN:
KAS-70-35-A-M32-Y3-NL

PNP:
KAS-80-35-A-M32-Y3-NL

- Non-Flush
- $S_d=2.....30$ mm
- M12 Connector
- M32 x 1.5 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 12.....30 VDC

M32 DC



NPN:
KAS-70-35-A-M32-NL

PNP:
KAS-80-35-A-M32-NL

- Non-Flush
- $S_d=2.....30$ mm
- 2m cable
- M32 x 1.5 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 12.....30 VDC

M18 AC




NO:
KAS-90-A23-S-NL

NC:
KAS-90-A23-O-NL

- Non-Flush
- $S_d=1.....10$ mm
- 2m cable
- M18 x 1 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 20.....250 V AC/DC

M30 AC



NO:
KAS-90-A24-S-NL

NC:
KAS-90-A24-O-NL

- Non-Flush
- $S_d=2.....20$ mm
- 2m cable
- M30 x 1.5 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 20.....250 V AC/DC

M32AC



NO:
KAS-90-32-S-M32-NL

NC:
KAS-90-32-O-M32-NL

- Non-Flush
- $S_d=3.....25$ mm
- 2m cable
- M32 x 1.5 Thread
- PA/PPO housing
- -13° F to +158° F
- NO+NC
- 20.....250 V AC/DC

