

# Redi-Lock® 300



**KURIYAMA INDUSTRIAL  
RUBBER HOSES**

**plastixs**  
manufacturing solutions

## Non-Conductive 300 PSI Push-On Hose

### General Applications:

- Air tools
- Low pressure pneumatic systems
- Robotic welders
- Water, oil and mild chemical solutions
- ★ Not recommended for unleaded gasoline

### Construction:

- **Cover** – Black Nitrile/PVC, RMA Class A oil resistant.
- **Reinforcement** – Aramid spiral yarn.
- **Tube** – Black Nitrile, RMA Class A oil resistant.

### Service Temperature Range:

-30°F (-34°C) to +180°F (+82°C)

### Features and Advantages:

- **Non-Conductive** - Tested to one (1) MEGOHM per inch resistance minimum.
- **MSHA approved flame resistant cover.**
- **Easy to couple.**
- **Long lengths on reels.**

### Branding:

REDI-LOCK NON-CONDUCTIVE  
300 PSI <size> MADE IN USA MSHA1C - 114/03

### Packaging:

Maximum 2 pcs. on reel.  
1/4" - 5/8" ID hoses supplied on plastic reels, 3/4"  
ID hoses supplied on wooden reels.

**Note:** For Push-On Fittings and Quick Disconnect Couplings refer to pages 15-17 of this catalog.



## Nominal Specifications

Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Reel Length (ft)	Weight (lbs/pc)
REDI-LOC-04X700	Black	1/4	1/2	300	700	70
REDI-LOC-06X700	Black	3/8	5/8	300	700	91
REDI-LOC-08X700	Black	1/2	3/4	300	700	112
REDI-LOC-10X700	Black	5/8	29/32	300	700	161
REDI-LOC-12X700	Black	3/4	1 1/32	300	700	182

Note: Cut lengths for this product are available from our Kuriyama Schaumburg, IL Warehouse location. Please call (847) 755-0360 or e-mail: sales@kuriyama.com for more information.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.