













Ureflex™

UFC[™] Series

Heavy Duty Polyurethane Lined Material Handling Hose

General Applications:

- Agricultural dry fertilizer
- Air seeder lines
- Industrial vacuum equipment
- Material handling heavy duty abrasive
- Milling machine scrap recovery
- Plastic processing equipment
- Shot blast recovery

Construction: PVC cover with polyurethane liner and rigid PVC helix.

Service Temperature:

-40°F (-40°C) to +150°F (+65°C)*

Features and Advantages:

- Thick Abrasion Resistant Polyurethane Liner -Designed for dry applications where severe abrasion is a factor. Provides for longer hose life and lower operating costs versus rubber or PVC hoses.
- Static Dissipative Cover Specially formulated to help prevent the build-up of static electricity for added safety and to help keep material flowing smoothly.
- Phthalate Free

UFC300

UFC400







- Transparent Construction "See-the-flow." Allows for visual confirmation of material flow.
- "Cold-Flex" Materials Hose remains flexible in sub-zero temperatures.
- Convoluted Outer Cover Provides increased hose flexibility.
- Oil Resistant Polyurethane Liner Resists most animal and petroleum based oils.

4

6

100

100

Nominal Specifications Min. Working Vacuum Bending Standard ID OD. Pressure (psi) Rating Hg (in) **Series** Radius Weight Length (mm) (in) (mm) (in) 68°F 104°F 68°F 104°F Number at 68°F (in) (ft) (lbs/ft) **UFC150** 1-1/2 38.1 1.85 47.0 50 25 Full 28 2 100 0.42 UFC200 2 50.8 2.40 61.0 40 20 Full 28 3 100 0.59 **UFC250** 2 - 1/263.5 3.07 78.0 40 20 Full 28 3 100 0.80

40

35

20

18

Full

Full

28

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

92.5

120.9

3.64

4.76

NOTE: For details of the following compliances, refer to footnotes listed on page 63.

*Actual service temperature range is application dependent.

76.2

101.6

PHTHALATE FREE⁽¹⁰⁾. RoHS⁽¹¹⁾

3

1.18

1.95