



Bridge Clamp with integrated grounding for attaching externally corrugated spiral hoses

Properties

- grounding without exposing spiral and without damaging hose
- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable
- conforms to RoHS guideline

Design, material

Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; bridge: stainless steel 1.4301 = AISI 304 (INOX); earthing screw: stainless steel (INOX)

Delivery variants

- further diameters available on request

Suitable for hose

AIRDUC®: 341 + 345 + 363; 351 + 355 (FOOD / INOX FOOD-AS / HT / EC); 355 AS; 362 (FOOD / EC);
TIMBERDUC®: 533 AS

Suitable for hose I.D. Inch	Clamping range Inch	Band width Inch	Order No.
1.50 - 1.75	1.36 - 2.17	0.35	212-0035-2878
2.00 - 2.17	1.75 - 2.50	0.35	212-0045-2878
2.36 - 2.50	2.17 - 3.00	0.35	212-0055-2878
2.76 - 3.00	2.50 - 3.35	0.35	212-0065-2878
3.15 - 3.35	3.00 - 3.74	0.35	212-0075-2878
3.50 - 3.74	3.35 - 4.13	0.35	212-0085-2878
4.00 - 4.13	3.74 - 4.50	0.35	212-0095-2878
4.33 - 4.50	4.13 - 5.00	0.35	212-0105-2878
4.72 - 5.00	4.50 - 5.31	0.35	212-0115-2878
5.12 - 5.31	5.00 - 5.71	0.35	212-0125-2878
5.50 - 5.71	5.31 - 6.10	0.35	212-0135-2878
6.00 - 6.10	5.71 - 6.50	0.35	212-0145-2878
6.30 - 6.50	6.10 - 6.89	0.35	212-0155-2878
6.69 - 6.89	6.50 - 7.28	0.35	212-0165-2878
7.48 - 7.68	7.28 - 8.07	0.35	212-0185-2878
8.00 - 8.07	7.68 - 8.46	0.35	212-0195-2878
8.27 - 8.46	8.07 - 8.86	0.47	212-0205-2878
8.66 - 8.86	8.46 - 9.25	0.47	212-0215-2878
9.84 - 10.04	9.65 - 10.43	0.47	212-0245-2878
10.63 - 10.83	10.43 - 11.22	0.47	212-0265-2878
11.00 - 11.22	10.83 - 11.61	0.47	212-0275-2878
11.81 - 12.00	11.61 - 12.40	0.47	212-0295-2878
12.60 - 12.80	12.40 - 13.19	0.47	212-0315-2878
13.78 - 13.98	13.58 - 14.37	0.47	212-0345-2878
14.96 - 15.16	14.76 - 15.55	0.47	212-0375-2878
15.75 - 15.94	15.55 - 16.34	0.47	212-0395-2878
17.72 - 17.91	17.52 - 18.31	0.47	212-0445-2878
19.69 - 19.88	19.49 - 20.28	0.47	212-0495-2878

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 68°F. We reserve the right to make technical changes. Please also refer to our Technical Appendix at www.norres.com.

We reserve the right to make technical changes. All values have been determined at 68°F and are approx. values.

Accessories



CONNECT 270-271

Distributed By: **plastixs**[®]
manufacturing solutions

151 Memorial Drive, Suite H
Shrewsbury, MA 01545

888-792-2223

www.plastixs.com

sales@plastixs.com

We reserve the right to make technical changes. All values have been determined at 68°F and are approx. values.