



Bridge Clamp with quick-release closure for attaching externally corrugated spiral hoses

Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable

- re-usable

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Design

- Quality: W2; clamp strip: stainless steel 1.4016 = AISI 430; clamp wire: stainless steel 1.4310 = AISI 301 (INOX); screw: chromated steel; Body: stainless steel 1.4016 = AISI 430

Delivery variants

- further diameters available on request

Suitable for hose I.D.	Band width	Order No.
(in)	(in)	
60	0.354	213-0060-0000
70	0.354	213-0070-0000
75	0.354	213-0075-0000
80	0.354	213-0080-0000
90	0.354	213-0090-0000
100	0.354	213-0100-0000
110	0.354	213-0110-0000
115	0.354	213-0115-0000
120	0.354	213-0120-0000
125	0.354	213-0125-0000
130	0.354	213-0130-0000
140	0.354	213-0140-0000
150	0.354	213-0150-0000
160	0.354	213-0160-0000
175	0.354	213-0175-0000
180	0.354	213-0180-0000
200	0.354	213-0200-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 68°F and are approx. data.

Accessories



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 68°F and are approx. data.