



Soft sleeve to slide onto connectors or push into pipes

Applications

- industrial vacuum cleaners, vacuum cleaners
- municipal vehicle: sweeper, sweeping machine
- municipal vehicle: lawn mower, slope mower, leaf blower/ leaf collector
- scrubber, floor cleaning machine

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas- and liquid-tight as pre-fitted version
- highly abrasion resistant
- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals

- version 241 - permanently antistatic wall: electrical and surface resistance approx. $10^9 \Omega$
- conforms to RoHS guideline

Temperature range

- -40°F to 195°F
- short time to 255°F

Design, material

wall: special premium ether-polyurethane (Pre-PUR[®])

Delivery variants

- further diameters available on request

- black (standard)
- special colors: full colored
- gas- and liquid-tight as pre-fitted version

Suitable for hose

AIRDUC[®]: 341 + 345; 350 (AS / AS BLACK / FOOD-AS); 351 + 355 + 356 (FOOD / INOX FOOD-AS / EC); 355 (SWEEPER / SWEEPER REINFORCED / VAC-TRUCK REINFORCED); 355 + 356 AS;
 TIMBERDUC[®]: 533 AS

Recommended adapter-Ø	Rec. Adapter length	Threading depth of hose	Total length	Weight	Suitable for hose I.D.	Order No.
inch	inch	inch	(Inch)	lbs/pcs	inch	
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
1.25	1.73	1.57	3.35	0.15	1.25	241-0032-8500
1.50	1.73	1.57	3.35	0.19	1.50	240-0038-0000
1.57	1.73	1.57	3.35	0.19	1.57	240-0040-0000
2.00	1.93	1.61	3.54	0.20	2.00	240-0050-0000
2.36	1.93	1.61	3.54	0.26	2.36	240-0060-0000
2.76	2.05	1.73	3.94	0.32	2.76	240-0070-0000
3.00	2.36	1.85	4.21	0.44	3.00	241-0075-8500
3.15	2.36	2.05	4.41	0.55	3.15	241-0080-8500
4.00	2.56	2.24	4.80	0.68	4.00	241-0100-8500
5.00	2.95	2.44	5.39	1.06	5.00	241-0125-8500
6.00	3.35	2.76	6.10	1.50	6.00	241-0150-8500
8.00	3.94	3.15	7.09	2.43	8.00	241-0200-8500
9.84	4.13	3.54	7.68	3.31	9.84	241-0250-8500
11.81	4.50	3.94	8.46	4.98	11.81	241-0300-8500
Threaded; Suitable for Hose 356						
1.50	1.73	1.57	3.35	0.15	1.50	241-0038-8501
1.57	1.73	1.57	3.35	0.18	1.57	241-0040-8501
2.00	1.93	1.61	3.54	0.18	2.00	241-0050-8501
2.36	1.93	1.61	3.54	0.26	2.36	241-0060-8501
2.76	2.05	1.73	3.94	0.33	2.76	241-0070-8501
3.00	2.36	1.85	4.21	0.44	3.00	241-0075-8501
3.15	2.36	2.05	4.41	0.55	3.15	241-0080-8501
4.00	2.56	2.24	4.80	0.68	4.00	241-0100-8501
5.00	2.95	2.44	5.39	1.06	5.00	241-0125-8501
6.00	3.35	2.76	6.10	1.50	6.00	241-0150-8501
8.00	3.94	3.15	7.09	2.43	8.00	241-0200-8501
9.84	4.13	3.54	7.68	3.31	9.84	241-0250-8501

Further technical data at www.norres.com. We reserve the right to make technical changes. All values have been determined at 68°F and are approximate values.

Recomended adapter-Ø inch	Rec. Adapter length inch	Threading depth of hose inch	Total length (Inch)	Weight lbs/pcs	Suitable for hose I.D. inch	Order No.
11.81	4.50	3.94	8.46	4.98	11.81	241-0300-8501
pre-fitted						
1.50	1.73	1.57	3.35	0.15	1.50	241-0038-8551
1.57	1.73	1.57	3.35	0.18	1.57	241-0040-8551
2.00	1.93	1.61	3.54	0.18	2.00	241-0050-8551
2.36	1.93	1.61	3.54	0.26	2.36	241-0060-8551
2.76	2.05	1.73	3.94	0.33	2.76	241-0070-8551
3.00	2.36	1.85	4.21	0.44	3.00	241-0075-8551
3.15	2.36	2.05	4.41	0.55	3.15	241-0080-8551
4.00	2.56	2.24	4.80	0.68	4.00	241-0100-8551
5.00	2.95	2.44	5.39	1.06	5.00	241-0125-8551
6.00	3.35	2.76	6.10	1.50	6.00	241-0150-8551
8.00	3.94	3.15	7.09	2.43	8.00	241-0200-8551
9.84	4.13	3.54	7.68	3.31	9.84	241-0250-8551
11.81	4.50	3.94	8.46	4.98	11.81	241-0300-8551

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 68°F. We reserve the right to make technical changes. Please also refer to our Technical Appendix at www.norres.com.

Distributed By: 

151 Memorial Drive, Suite H
Shrewsbury, MA 01545
888-792-2223
www.plastixs.com
sales@plastixs.com