



Soft sleeve to slide onto connectors or push into pipes, electrically conductive

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant
- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- electrically conductive wall: electrical and surface resistance $<10^3 \Omega$

- conforms to RoHS guideline

Temperature range

- -40°F to 195°F
- short time to 255°F

Design, material

Wall of EC version electrically conductive $<10^3 \Omega$: electrically conductive premium ester-polyurethane (Pre-PUR[®])

Delivery variants

- further diameters available on request
- black (standard)
- special colors: full colored

Suitable for hose

AIRDUC[®]: 350 (AS / AS BLACK / FOOD-AS); 351 + 355 (FOOD / INOX FOOD-AS / EC)
 TIMBERDUC[®]: 533 AS

Recommended adapter-Ø in	Rec. Adapter length	Threading hepth of hose	Total length (Inch)	Weight lbs/pcs	Suitable for hose I.D. Inch	Order No.
1.50	1.73	1.57	3.35	0.21	1.50	240-0038-1003
1.57	1.73	1.57	3.35	0.19	1.57	240-0040-1003
2.00	1.93	1.61	3.54	0.23	2.00	240-0050-1003
2.36	1.93	1.61	3.54	0.29	2.36	240-0060-1003
2.76	2.05	1.73	3.78	0.36	2.76	240-0070-1003

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 68°F. We reserve the right to make technical changes. Please also refer to our Technical Appendix at www.norres.com.

Distributed By: **plastixs**[®]
 manufacturing solutions

151 Memorial Drive, Suite H
 Shrewsbury, MA 01545
 888-792-2223
www.plastixs.com
sales@plastixs.com