



Metal hose connector / reducer

Properties

- easily and quickly fitted
- re-usable (threaded version)
- conforms to RoHS guideline

- REACH according to--> Technology/
Technical Information / REACH

Temperature range

- 390 ° F

Design

- galvanized sheet metal

Delivery variants

- further diameters available on request
- stainless steel (INOX)

Suitable for Hose O-D1 (In)	Suitable for Hose O-D2 (In)	Adapter length L1 (In)	Adapter length L2 (In)	Total Length (In)	Wall thickness (In)	Weight (lb/pcs)	Order No.
Hose connector							
1.969	1.969	1.575	1.575	0.000	0.024	0.441	270-0050-0000
2.362	2.362	1.575	1.575	0.000	0.024	0.441	270-0060-0000
2.756	2.756	1.575	1.575	0.000	0.024	0.441	270-0070-0000
2.953	2.953	1.575	1.575	0.000	0.024	0.441	270-0075-0000
3.150	3.150	1.575	1.575	0.000	0.024	0.441	270-0080-0000
3.543	3.543	1.575	1.575	0.000	0.024	0.441	270-0090-0000
3.937	3.937	1.575	1.575	0.000	0.024	0.441	270-01 00-0000
4.331	4.331	1.575	1.575	0.000	0.024	0.662	270-0110-0000
4.724	4.724	1.575	1.575	0.000	0.024	0.662	270-01 20-0000
4.921	4.921	1.575	1.575	0.000	0.024	0.662	270-01 25-0000
5.118	5.118	1.575	1.575	0.000	0.024	0.662	270-01 30-0000
5.512	5.512	1.575	1.575	0.000	0.024	0.882	270-0140-0000
5.906	5.906	1.575	1.575	0.000	0.024	1.103	270-0150-0000
6.299	6.299	1.575	1.575	0.000	0.024	1.103	270-01 60-0000
6.693	6.693	1.575	1.575	0.000	0.024	1.103	270-01 70-0000
6.890	6.890	1.575	1.575	0.000	0.024	1.323	270-0175-0000
7.087	7.087	1.575	1.575	0.000	0.024	1.323	270-0180-0000
7.874	7.874	1.575	1.575	0.000	0.024	1.323	270-0200-0000
8.465	8.465	1.575	1.575	0.000	0.024	1.544	270-0215-0000
8.858	8.858	1.575	1.575	0.000	0.024	1.544	270-0225-0000
9.843	9.843	2.362	2.362	0.000	0.024	1.764	270-0250-0000
10.827	10.827	2.362	2.362	0.000	0.024	1.985	270-0275-0000
11.811	11.811	2.362	2.362	0.000	0.028	2.205	270-0300-0000
12.402	12.402	2.362	2.362	0.000	0.028	2.426	270-0315-0000
12.795	12.795	2.362	2.362	0.000	0.028	2.646	270-0325-0000
13.780	13.780	2.362	2.362	0.000	0.028	2.867	270-0350-0000
14.764	14.764	3.150	3.150	0.000	0.028	3.308	270-0375-0000
15.748	15.748	3.150	3.150	0.000	0.028	3.528	270-0400-0000
17.717	17.717	3.150	3.150	0.000	0.028	4.631	270-0450-0000
19.685	19.685	3.150	3.150	0.000	0.028	5.072	270-0500-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 68 ° F and are approx. data.

Suitable for Hose O-D1 (In)	Suitable for Hose O-D2 (In)	Adapter length L1 (In)	Adapter length L2 (In)	Total Length (In)	Wall thickness (In)	Weight (lb/pcs)	Order No.
Hose reduction							
2.953	1.969	1.575	1.575	0.000	0.024	0.441	271-0075-0000
3.150	2.756	1.575	1.575	0.000	0.024	0.441	271-0080-0000
3.150	1.969	1.575	1.575	0.000	0.024	0.441	271-0080-2655
3.937	3.150	1.575	1.575	0.000	0.024	0.441	271-01 00-0000
3.937	2.756	1.575	1.575	0.000	0.024	0.441	271-01 00-2660
4.921	3.937	1.575	1.575	0.000	0.024	0.662	271-0125-0000
4.921	3.150	1.575	1.575	0.000	0.024	0.662	271-01 25-2665
5.906	3.937	1.575	1.575	0.000	0.024	0.662	271-01 50-0000
5.906	3.150	1.575	1.575	0.000	0.024	0.882	271-0150-2670
5.906	4.921	1.575	1.575	0.000	0.024	0.662	271-01 50-2671
7.874	5.906	1.575	1.575	0.000	0.024	1.103	271-0200-0000
7.874	3.937	1.575	1.575	0.000	0.024	1.323	271-0200-2675
7.874	4.921	1.575	1.575	0.000	0.024	1.323	271-0200-2676
9.843	7.874	2.362	1.575	0.000	0.024	1.764	271-0250-0000
9.843	4.921	2.362	1.575	0.000	0.024	2.205	271-0250-2680
9.843	5.906	2.362	1.575	0.000	0.024	1.985	271-0250-2681
11.811	7.874	2.362	1.575	0.000	0.028	2.646	271-0300-0000
11.811	5.906	2.362	1.575	0.000	0.028	2.867	271-0300-2685
11.811	9.843	2.362	1.575	0.000	0.028	2.867	271-0300-2687

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 68 ° F and are approx. data.

Accessories



CLAMP 211



CLAMP 212



CONNECT228



CLAMP 217

Distributed By: 

151 Memorial Drive, Suite H
Shrewsbury, MA 01545
888-792-2223

www.plastixs.com
sales@plastixs.com

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 68 ° F and are approx. data.