

Polyethylene clamp profile hose (clip hose)

Applications

- flexible hose/ ducting for gases and for dust, powder, fibers
- chemical industry: chemical vapors, vapor return hose at loading arm, paint steam, spray mist extraction
- asbestos removal
- construction drying

Properties

- abrasion protection via external clamp profile
- secure clamping of the wall within the clamp profile
- highly flexible + compressible 4:1
- odorless and tasteless
- good resistance to alkalis and acids
- extremely good resistance to chemicals
- conforms to RoHS guideline

Temperature range

- -30°F to 175°F

Design, material

CP construction

1. clamp profile supporting spiral: galvanized steel
2. wall: polyethylene fabric (LDPE + HDPE)

Delivery variants

- further diameters and lengths available on request
- stainless steel (INOX) clamp profile
- double-layer

I.D. in / mm	O.D. in	Pressure psi	Vacuum inHG	Bending Radius in	Weight lbs./ft	Stock length ft	Production Length ft	Further production lengths ft	Order No.
2 / 50-51	2.44	7.10	7.97	0.71	0.30	25	-	-	457-0050-0000
- / 55	2.64	6.65	7.38	3/4	0.32	25	-	-	457-0055-0000
2.36 / 60	2.83	6.40	6.50	0.79	0.34	-	25	-	457-0060-0000
2.5 / 63-65	3.03	6.10	5.91	0.85	0.36	25	-	-	457-0065-0000
- / 70	3.20	5.80	5.32	7/8	0.40	25	-	-	457-0070-0000
3 / 75-76	3.43	5.50	4.72	0.93	0.42	25	-	-	457-0075-0000
- / 80	3.62	5.30	4.13	0.94	0.45	-	25	-	457-0080-0000
3.5 / 89-90	4.00	4.95	2.95	1.02	0.50	25	-	-	457-0090-0000
4 / 100-102	4.41	3.25	2.51	1.10	0.36	25	-	-	457-0100-0000
- / 110	4.80	3.05	2.21	1 1/8	0.39	-	12.5 25	-	457-0110-0000
4.5 / 114-115	5.00	2.95	2.07	1.24	0.41	12.5 25	-	-	457-0115-0000
4.72 / 120	5.20	2.90	1.92	1.25	0.43	-	12.5 25	-	457-0120-0000
5 / 125-127	5.39	2.85	1.77	1.32	0.44	12.5 25	-	-	457-0125-0000
- / 130	5.59	2.60	1.62	1.34	0.46	12.5 25	-	-	457-0130-0000
5.5 / 140	6.00	2.60	1.18	1.42	0.50	12.5 25	-	-	457-0140-0000
6 / 150-152	6.38	1.75	1.03	1.50	0.53	12.5 25	-	-	457-0150-0000
6.3 / 160	6.77	1.65	0.89	1.57	0.57	-	12.5 25	-	457-0160-0000
6.5 / 165	6.97	1.60	0.89	1.61	0.58	12.5 25	-	-	457-0165-0000
- / 170	7.17	1.60	0.89	1.65	0.60	-	12.5 25	-	457-0170-0000
- / 175	7.36	1.60	0.89	1.71	0.61	12.5 25	-	-	457-0175-0000
7 / 178-180	7.56	1.60	0.74	1.73	0.63	12.5 25	-	-	457-0180-0000
8 / 200-203	8.35	1.45	0.59	1.89	0.54	12.5 25	-	-	457-0200-0000
- / 215	8.94	1.40	0.59	2.03	0.58	12.5 25	-	-	457-0215-0000
- / 225	9.33	1.30	0.59	2.11	0.60	-	12.5 25	-	457-0225-0000
9 / 228-229	9.45	1.15	0.59	2.13	0.60	12.5 25	-	-	457-0228-0000
- / 250	10.31	1.00	0.44	2.28	0.66	-	12.5 25	-	457-0250-0000
10 / 254	10.47	0.95	0.44	2.32	0.67	12.5 25	-	-	457-0254-0000
- / 275	11.30	0.85	0.44	2.50	0.73	12.5 25	-	-	457-0275-0000
11 / 280	11.50	0.85	0.44	2.54	0.75	12.5 25	-	-	457-0280-0000
- / 300	12.28	0.85	0.30	2.68	0.80	-	12.5 25	-	457-0300-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

I.D. in / mm	O.D. in	Pressure psi	Vacuum inHG	Bending Radius in	Weight lbs./ft	Stock length ft	Production Length ft	Further production lengths ft	Order No.
12 / 305	12.48	0.80	0.30	2.72	0.81	12.5 25	-	-	457-0305-0000
- / 315	12.87	0.75	0.30	2.78	0.84	12.5 25	-	-	457-0315-0000
- / 325	13.27	0.65	0.30	2.89	0.87	12.5 25	-	-	457-0325-0000
13 / 330	13.46	0.65	0.30	2.93	0.88	12.5 25	-	-	457-0330-0000
- / 350	14.25	0.65	0.30	3.07	0.93	-	12.5 25	-	457-0350-0000
14 / 356	14.49	0.60	0.30	3.11	0.95	12.5 25	-	-	457-0356-0000
- / 375	15.24	0.60	0.30	3.25	1.00	12.5 25	-	-	457-0375-0000
- / 400	16.22	0.60	0.15	3.46	1.10	-	12.5 25	-	457-0400-0000
16 / 405-406	16.46	0.50	0.15	3.50	1.07	12.5 25	-	-	457-0406-0000
- / 450	18.19	0.50	0.15	3.86	1.19	-	12.5 25	-	457-0450-0000
18 / 457	18.46	0.50	0.15	3.92	1.21	12.5 25	-	-	457-0457-0000
- / 500	20.16	0.35	0.15	4.25	1.32	-	12.5 25	-	457-0500-0000
20 / 508	20.47	0.35	0.15	4.31	1.34	12.5 25	-	-	457-0508-0000
- / 600	24.09	0.35	0.15	5.04	1.59	-	12.5 25	-	457-0600-0000
24 / 610	24.49	0.35	0.15	5.12	1.62	12.5 25	-	-	457-0610-0000
- / 700	28.00	0.30	0.06	5.83	1.84	-	12.5 25	-	457-0700-0000
28 / 712	28.50	0.30	0.03	5.93	1.87	12.5 25	-	-	457-0712-0000
- / 750	30.00	0.30	0.03	6.22	1.96	12.5 25	-	-	457-0750-0000
- / 800	31.97	0.20	0.03	6.61	2.10	-	12.5 25	-	457-0800-0000
32 / 813-815	32.56	0.20	0.03	6.73	2.14	12.5 25	-	-	457-0815-0000
- / 900	35.91	0.20	0.03	7.40	2.36	-	12.5 25	-	457-0900-0000
36 / 915	36.50	0.20	0.03	7.52	2.40	12.5 25	-	-	457-0915-0000
- / 1000	39.84	0.20	0.03	8.19	2.62	-	12.5 25	-	457-1000-0000
40 / 1016	40.47	0.20	0.03	8.31	2.66	12.5 25	-	-	457-1016-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only. Additional information at www.norres.com/us/technology-us/

Accessories




CLAMP 212



CLAMP 217



CLAMP 213



CONNECT 228



CONNECT 270-271

Distributed By: **plastixs**[®]
manufacturing solutions

151 Memorial Drive, Suite H
Shrewsbury, MA 01545
888-792-2223

www.plastixs.com
sales@plastixs.com

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.