







PTFE hose/tubing

### Applications

- flexible hose/ ducting for liquids and for gases
- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- · heating hose: interior hose for media transfer

### **Properties**

- · highly flexible
- food grade wall, complies with: FDA 21 CFR 177.2600, German guideline XV BfR

- odorless and tasteless
- · anti-adhesive
- microbe and hydrolysis resistant
- good resistance to alkalis and acids
- extremely good resistance to chemicals
- conforms to RoHS guideline

### Temperature range

-240°F to 390°F

# Design, Material

NORFLEX® design

1. wall interior and exterior smooth; wall: PTFE

#### Delivery variants

- further diameters and lengths available on request
- transparent (standard)

I.D. in / mm	Wall thickness Inch	O.D. in	Over- pressure psi	Weight lbs./ft	Stock length ft	Order No.
-/2	0.04	0.16	217.55	0.020	150	407-9020-0000
1/8/3	0.04	0.20	217.55	0.030	150	407-9030-0000
-/4	0.04	1/4	145.05	0.035	150	407-9040-0000
1/4 / 6	0.04	5/16	145.05	0.050	150	407-9060-0000
5/16 / 8	0.04	3/8	72.50	0.060	150	407-9080-0000
3/8 / 10	0.04	0.47	72.50	0.075	150	407-9100-0000
-/12	0.04	0.55	72.50	0.090	150	407-9120-0000
-/14	0.04	5/8	72.50	0.105	150	407-9140-0000

## Accessories



CLAMP 208



151 Memorial Drive, Suite H Shrewsbury, MA 01545 888-792-2223

www.plastixs.com sales@plastixs.com

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.