

# TECHNICAL DATA SHEET

## Quick Lecithin Release Aerosol 44812



### Product Description

Quick Lecithin imparts a smooth, dry film so you can begin production immediately. Lecithin is food-approved and paintable. Non-silicone formula will not interfere with part bonding, heat sealing, laminating, ultrasonic welding or post-decorating.

### Applications

Mold Release

### Unit Package Description

16 ounce can

### Generic Description

Paintable Mold Release

### Net Weight Fill

11.5 net ounces

### UPC Code

858799000486

### Units Per Case

12

### Case Weight (lbs)

13

### Appearance

Clear Oily Colorless Liquid

### Flash Point F

Not Determined

### Flash Point C

Not Determined

### Base Type

Lecithin

### Evaporation Rate

Fast

### Working Temperature F

32 to 500 degrees

### Working Temperature C

0 to 260 degrees

### Propellant

DME/152A

### NFPA Aerosol

### Flammability Level

3

### DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

### VOC % (Federal)

68

### VOC g/L (Federal)

535.78

### VOC lbs./Gal (Federal)

4.47

### Removal

Remove with organic or hydrocarbon solvents

### Food Safety Citation (CFR)

21CFR 184.1400