

SAFETY DATA SHEET

Product Name: Slide NPT Purging Compound

Issue Date: 01-March-2015 Revision Date: 01-March-2022 Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

SDS # 451 (OSHA)

Product Code451-05, 451-45, & 451-1300Product NameSlide NPT Purging Compound

Synonyms NPT Formula 451

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use Industrial purging compound

1.3. Details of the Supplier of the Safety Data Sheet

Supplier

Slide Products Inc. 430 S. Wheeling Road Wheeling, IL 60090

For further information, please contact

Contact Point Slide Products: 1-847-541-7220, 800-323-6433

Email Address info@slideproducts.com

1.4. Emergency telephone number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. Hazard Information

GHS CLASSIFICATION:

NOT A HAZARDOUS SUBSTANCE OR MIXTURE.

Emergency Overview

GHS LABEL ELEMENTS:

PICTOGRAMS: NONE SIGNAL WORD: NONE

HAZARD STATEMENTS: NONE

Color: White – Grayish White

Physical State: Pellet

Odor: Mild Sweet Odor Hazards of Slipping hazard

Product:

Potential Health Effects

Eye Contact: Solid or dust may cause irritation or corneal injury due to mechanical

action. Elevated temperatures may generate vapour levels sufficient to

cause eye irritation. Effect may include discomfort and redness

N/A

Skin Contact: Under elevated temperatures, contact with the material may cause

thermal burners

Inhalation: Under elevated temperatures, vapours / fumes released during thermal

processing may cause respiratory irritation

Ingestion: Low toxicity

3. Composition / Information On Ingredients

Components: Trade Secret, HDPE-base

Inorganic Salts
Inert minerals

Thermoplastic Polyolefin

All component(s) comprising this product are either exempt or listed on the TSCA inventory.

4. First Aid Measure

Eye Contact Flush eyes thoroughly with water for several minutes.

Skin Contact If molten material comes in contact with the skin, do not apply ice but

cool under running stream of water. DO NOT attempt to remove the material from the skin. Removal could result in severe tissue damage.

Seek medical attention immediately

Inhalation Ingestion

Move person to fresh air; if effects occur or continue, consult a physician

If swallowed, seek medical attention. May cause gastrointestinal

blockage. Do not give laxatives. Do not induce vomiting unless directed

by medical

5. Fire Fighting Measures

Extinguishing Water fog or fine spray. Carbon Dioxide fire extinguisher. Foam

Media

Fire Fighting Keep people away. Isolate fire and deny unnecessary entry. Soak **Procedures** thoroughly with water to cool and prevent re-ignition. If material is

molten, do not apply direct water stream. Use fine water spray or

foam. Cool surroundings with water to localize fire zone.

Special Protective Equipment for Firefighters Wear positively-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing. If protective equipment is not available or not used, fight fire from a protected location or safe

distance

Unusual Fire and Explosion hazard

Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions,

do not permit dust to accumulate

6. Accidental Release Measures

Step to be taken if Material is released or Spilled: Contained the spilled material if possible. Sweep up. Collect in suitable and properly labeled containers

Personal Spilled material may cause a slip hazard. Use appropriate safety

Precautions: equipment

Environmental Precautions: Prevent from entering into soil, sewers, waterways and/or

groundwater

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING: HANDLE AS A THERMOPLASTIC RESIN. BEFORE INTRODUCE ULTRA PLAST IN THE MACHINE READ ALWAYS THE MSDS OF THE PRODUCT WHICH ULTRA PLAST WILL BE IN CONTACT WITH

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

STORE IN A COOL AND DRY AREA, NORMALLY VENTILATED MAKE SURE THAT THE BUCKET IS CLOSED AFTER TAKING OF QUANTITY NECESSARY FOR MORE OR LESS IMMEDIATE USE. THE FORMATION OF SMALL CLOTS OF STICKY SUBSTANCE DOES NOT AFFECT THE EFFICIENTCY OF THE PRODUCT; IT JUST SHOWS THE MOISTURE ABSORPTION INDEX. AVOID DIRECT CONTACT WITH ACETAL OR DELRYN RESINS.

8. Exposure Controls / Personal Protection

Exposure Limits Consult local authorities for recommended exposure limits

Personal Protection

Eye / Face Use safety glasses.

Protection

Skin Protection Clean body-covering clothing. Gloves – selection will depend on the

task. Insulated gloves maybe required for thermal protection

Respiratory Respiratory protection should be worn when there is a potential to

Protection exceed the exposure limit requirements or guideline

Ingestion Use good personal hygiene. Do not consume or store food in the work

area. Wash hands before smoking or eating.

9. Physical and Chemical Properties

Physical Pellets

Colour White – Grayish White

Odour None noted

Flash Point
N/A (not applicable)
Flammable Limits
N/A (not applicable)

Specific Gravity 5.84 lb./gal.

Freezing Point

Solubility in Water negligible

pH N/A (not applicable) **Decomposition Temperature** > 280° F (>138°C)

10. Stability and Reactivity

Stability Stable at temperatures below 280°F.

Hazardous Will not occur

Polymerization

Thermal Decomposition At temperature exceeding the melt temperature, fumes / vapour

can be released. Fumes can be irritating.

Materials to Avoid Acids, Alkalis, Halides. Combustible materials, Oxidizing

materials and Reducing agents. Acetal or Delryn resins.

11. Toxicological Information

Acute Toxicity

Ingestion Low toxicity

Skin Absorption May cause skin irritation

Inhalation Airborne dust may be irritating to eyes, nose, lungs, throat upon

contact

Chronic Toxicity

Carcinogenicity Ingredients are Not on IRAC or ACGIH listing

12. Ecological Information

Ecotoxicological

Fish Species 2000 mg / liter LC50 (Lepomis macrochirus) 96 hours

2000 mg / liter LC50 (Oncorhynchus mykiss) 96 hours

Acute CrustaceansNot availableFreshwater AlgaeNot available

13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. Landfill.

14. Transportation Information

TDG small container
TDG Large container
IMDG
ICAO / IATA
Not regulated
Not regulated
Not regulated
Not regulated

15. Regulatory Information

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

Hazardous Products Act Information: CPR Compliance

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Hazardous Products Act Information: WHMIS Classification

This product is not a "Controlled Product" under WHMIS.

16. Other Information

Issue Date:01-March-2015Revision Date:01-March-2022Revision Note:New part sizes

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet