

# Material Handling

**ALFAGOMMA®**

**plastixs®**  
manufacturing solutions

## **HWT763AA** 75 PSI Heavy Duty Dry Powder Delivery Hose 3/8" Tube



### **Applications:**

Discharge of dry powders under low pressure.  
Pneumatic transfer of dry materials and abrasive slurries.

### **Cover:**

Black conductive SBR/NR blend – abrasion and ozone resistant.

### **Reinforcement:**

Spiraled high tensile textile cords.

### **Tube:**

3/8" black static conducting NR – compounded to resist cutting by abrasive materials.

### **Working Pressure:**

Constant Pressure – 5 Bar (75 PSI)

### **Temperature Range:**

-22°F (-30°C) to 176°F (+80°C)

### **Branding:**

ALFAGOMMA – ITALY T763 5 BAR (75 PSI) HEAVY DUTY BULK MATERIAL DELIVERY (in green letters)

### **Standard Length:**

100 feet

## **Nominal Specifications**

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
HWT763AA400	4	102	4.96	126	75	2.56

★ Excessive bending during operation may cause premature wear.

### **COUPLING SUGGESTIONS**

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.