



T204AA 75 PSI SBR Water S & D Hose

Applications:

Suction and discharge of water for irrigation and construction.

Cover:

Black SBR – ozone and abrasion-resistant.

Reinforcement:

Spiraled high tensile textile cords with flexible steel helix wire.

Tube:

Black SBR.

Working Pressure:

Constant Pressure – 5 Bar (75 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Branding:

ALFAGOMMA– ITALY – T204 (embossed)

Standard Length:

20, 25, 50, 100 feet: 6"
20, 25, feet: 8"

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Vacuum HG (in.)	Min. Bending Radius (in. @ 68°F)	Weight (lbs./ft.)
T204AA600	6	152	6.54	166	75	24	30	4.13
T204AA800	8	203	8.70	221	75	21	40	7.06

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.