



T351LL
White
Cover

T351LG
Green
Cover

plastiXs®
manufacturing solutions

T351LL / T351LG 150 PSI Premium Paper Mill/Creamery Wash Down Hose With Tapered Nozzle

3-A
COMPLIANT MATERIAL

Applications:

For general wash down service, using hot and cold water in paper mills and in food and dairy plants.

Cover:

White or green EPDM – heat, abrasion and ozone resistant.

Reinforcement:

High tensile textile cords.

Tube:

White EPDM. Meets FDA and 3A (18-03) requirements.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Temperature Range:

-40°F (-40°C) to 248°F (+120°C)

Standard Length:

50 feet including 6" long built-in tapered nozzle*

***Tapered Nozzle Hole Size**

3/4" and 1" ID 3/8"
1 1/4" ID 1/2"
1 1/2" ID 5/8"

*T351 fully complies with the requirements listed in FDA CFR21.

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T351LL/LG075	3/4	19	1.22	31	150	0.44
T351LL/LG100	1	25	1.46	37	150	0.54
T351LL/LG125	1 1/4	32	1.81	46	150	0.78
T351LL/LG150	1 1/2	38	2.05	52	150	0.91

COUPLING SUGGESTIONS

Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.