



## T653AA

### Soft Wall Marine Exhaust Hose – SAE J2006 R1



#### Applications:

Marine wet exhaust and bilge pump connections.

#### Cover:

Black Synthetic Rubber – abrasion, ozone and hydrocarbon resistant.

#### Reinforcement:

High tensile textile cords.

#### Tube:

Black Synthetic Rubber.

#### Working Pressure:

Constant Pressure – 5 Bar (75 PSI)

#### Temperature Range:

-22°F (-30°C) to 212°F (+100°C)

#### Branding:

ALFAGOMMA – ITALY – T653 SOFT WALL MARINE WET EXHAUST SAE J2006 R1 <SIZE> <YYYY MFG> (in blue letters)

#### Standard Length:

12 1/2 feet in straight lengths

### Nominal Specifications

| Series    | ID (in.) | ID (mm) | OD (in.) | OD (mm) | Max Rec. WP (PSI) | Weight (lbs./ft.) |
|-----------|----------|---------|----------|---------|-------------------|-------------------|
| T653AA100 | 1        | 25      | 1.38     | 35      | 75                | 0.43              |
| T653AA112 | 1 1/8    | 28      | 1.50     | 38      | 75                | 0.47              |
| T653AA125 | 1 1/4    | 32      | 1.65     | 42      | 75                | 0.52              |
| T653AA137 | 1 3/8    | 35      | 1.77     | 45      | 75                | 0.56              |
| T653AA150 | 1 1/2    | 38      | 1.89     | 48      | 75                | 0.61              |
| T653AA162 | 1 5/8    | 42      | 2.05     | 52      | 75                | 0.66              |
| T653AA175 | 1 3/4    | 45      | 2.17     | 55      | 75                | 0.70              |
| T653AA189 | 1 7/8    | 48      | 2.28     | 58      | 75                | 0.75              |
| T653AA200 | 2        | 51      | 2.48     | 63      | 75                | 0.97              |
| T653AA225 | 2 1/4    | 57      | 2.72     | 69      | 75                | 1.07              |
| T653AA238 | 2 3/8    | 60      | 2.91     | 74      | 75                | 1.31              |
| T653AA250 | 2 1/2    | 63      | 3.03     | 77      | 75                | 1.37              |
| T653AA300 | 3        | 76      | 3.54     | 90      | 75                | 1.64              |
| T653AA350 | 3 1/2    | 90      | 4.09     | 104     | 75                | 1.95              |
| T653AA400 | 4        | 102     | 4.57     | 116     | 75                | 2.18              |

continued



**plastiXs®**  
manufacturing solutions

## **T653AA (continued)** Soft Wall Marine Exhaust Hose – SAE J2006 R1

### Nominal Specifications

| Series    | ID (in.) | ID (mm) | OD (in.) | OD (mm) | Max Rec. WP (PSI) | Weight (lbs./ft.) |
|-----------|----------|---------|----------|---------|-------------------|-------------------|
| T653AA450 | 4 1/2    | 115     | 5.08     | 129     | 75                | 2.43              |
| T653AA500 | 5        | 127     | 5.55     | 141     | 75                | 2.68              |
| T653AA600 | 6        | 152     | 6.61     | 168     | 75                | 3.26              |
| T653AA662 | 6 5/8    | 168     | 7.24     | 184     | 75                | 3.57              |
| T653AA800 | 8        | 203     | 8.70     | 221     | 75                | 4.96              |