



plastiXs®
manufacturing solutions

T760LE **75 PSI Dry Bulk Food** **Discharge Hose**

Applications:

Discharge or delivery of dry bulk food products.

Cover:

Blue SBR/EPDM – abrasion and ozone resistant.

Reinforcement:

Spiraled high tensile textile cords with static wire.

Tube:

3/16" white NR – abrasion resistant. Meets FDA requirements.

Working Pressure:

Constant Pressure – 5 Bar (75 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T760 5 BAR (75 PSI) – BULK FOOD & MATERIAL DELIVERY (in white letters)

Standard Length:

100 feet

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T760LE400	4	102	4.65	118	75	2.12

★ Please note: Proper grounding of static wire will prolong tube life.

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 36.

COUPLING SUGGESTIONS

Quick-Acting coupling attached with bands.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.