



plastiXs®
manufacturing solutions

T902AA 150 PSI High Quality Hot Air Blower Hose

Applications:

Hot air transfer between the air compressor and dry bulk tank on bulk material carriers.

Cover:

Black EPDM – heat, abrasion and ozone resistant.

Reinforcement:

Spiraled high tensile textile cords with flexible steel helix wire.

Tube:

Black EPDM – heat-resistant.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Temperature Range:

-40°F (-40°C) to 356°F (+180°C)

Branding:

ALFAGOMMA – ITALY T902 10 BAR (150 PSI) – HOT AIR SERVICE (in white letters)

Standard Length:

100 feet

Nominal Specifications

| Series | ID (in.) | ID (mm) | OD (in.) | OD (mm) | Max Rec. WP (PSI) | Vacuum HG (in.) | Min. Bending Radius (in. @ 68°F) | Weight (lbs./ft.) |
|-----------|----------|---------|----------|---------|-------------------|-----------------|----------------------------------|-------------------|
| T902AA200 | 2 | 51 | 2.48 | 63 | 150 | 30 | 6 | 1.01 |
| T902AA300 | 3 | 76 | 3.54 | 90 | 150 | 27 | 9 | 1.60 |
| T902AA400 | 4 | 102 | 4.57 | 116 | 150 | 27 | 12 | 2.23 |

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.