



**plastiXs**<sup>®</sup>  
manufacturing solutions

## **T957LL** **300 PSI Furnace Door** **Coolant Hose**

### **Applications:**

To convey cooling water to furnace doors in steel mills, glass plants, foundries, or where the hose is subjected to high temperatures and splashes of white-hot molten metals or glass.

### **Cover:**

Beige EPDM – heat resistant, non-conductive resin-coated dust-free fiberglass cover.

### **Reinforcement:**

High tensile textile cords.

### **Tube:**

White EPDM.

### **Working Pressure:**

Constant Pressure – 20 BAR (300 PSI)

### **Temperature Range:**

Tube: -40°F (-40°C) to 248°F (+120°C)

Cover: -40°F (-40°C) to 1000°F (up to +540°C)

### **Standard Length:**

100 feet

### **Nominal Specifications**

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T957LL050	1/2	13	0.98	25	300	0.30
T957LL075	3/4	19	1.22	31	300	0.46
T957LL100	1	25	1.46	37	300	0.56
T957LL125	1 1/4	32	1.81	46	300	0.82
T957LL150	1 1/2	38	2.13	54	300	0.98
T957LL200	2	51	2.64	67	300	1.26
T957LL250	2 1/2	63	3.19	81	300	1.55
T957LL300	3	76	3.78	96	300	2.15

★ Special order, minimums required. Contact your nearest KOA warehouse location for more information.