

FLEX-TUBE® VR-U VAPOR RECOVERY HOSE

The hose that won't leave you fuming

Flex-Tube® VR-U is a static dissipative UV resistant polyurethane blend hose reinforced with a UV resistant rigid external PVC helix and an embedded copper braided grounding wire

FEATURES:


- Resistant to all biofuel vapors including gasoline, diesel, biodiesel, ethanol at service stations and transfer terminals
- Rigid external helix offers external abrasion and drag resistance over rough surfaces
- Phthalate free with great ozone and abrasion resistance
- Lightweight and very easy to maneuver on and off the truck
- Enclosed copper grounding wire reduces static build-up in vapor recovery applications
- Surface Resistivity Level: 10^8 - 10^{10} Ohms/Square
- Banding coils available for smooth assembly attachment
- Temperature Range: -40°F to 160°F
- Size Range: 3", 4"
- Standard Length: 100'

ID (Inches)	Wall Thickness (Inches)	Working Pressure (PSI)	Vacuum (InHg)	CL Bend Radius (Inches)	OD Nominal (Inches)	Weight Per Foot (Lbs./Ft.)
3	.050	40	28	5	3.47	.72
4	.055	40	28	7	4.53	1.1

* Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate end user of the product. This information is presented as a guide only. The number of variables which can be present in any application make firm recommendations impossible.

** Application conditions will affect service temperature.

*** Vapor Use Only-Wire Must Be Earth Grounded Less Than 10 Ohms Per Applicable Regulations

California Residents:
 **WARNING:** Cancer and Reproductive Harm-www.P65Warnings.ca.gov



VR-U

VR-U with banding coil