



Ground Cover GC-C™ Series

Heavy-Duty, Polyurethane Lined, Material Handling Hose

GENERAL APPLICATIONS

- Material handling – heavy duty abrasive
- Mulch, bark, wood chips and other surfacing material delivery
- Soil, seed and compost delivery

CONSTRUCTION

PVC cover with polyurethane liner and rigid PVC helix

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +150°F (+65°C)*

*Actual service temperature range is application dependent.

FEATURES AND ADVANTAGES

- Abrasion Resistant Polyurethane Liner – Designed for dry applications where severe abrasion is a factor. Provides longer hose life and lower operating costs versus rubber or PVC hoses.
- “Cold-Flex” Materials – Hose remains flexible in sub-zero temperatures.
- Transparent Construction – “See-the-flow.” Allows for visual confirmation of material flow.
- Convoluted Outer Cover – Provides increased hose flexibility. Allows for easier unwinding and winding on hose reels.
- Oil Resistant Polyurethane Liner – Resists most animal and petroleum based oils.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F			
GC-C400	4	101.6	4.59	116.6	30	15	28	25	6	100	1.00
GC-C500	5	127.0	5.57	141.5	30	15	25	20	10	100	1.80

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.

COMPLIANCES (for details see page 87)

Phthalate Free (10), RoHS (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.