## **Morris Gaylord Vacuum Wands**



Unloading powders or pellets made easy with Morris Coupling's line of Gaylord Vacuum Wands. Seven models available in aluminum (standard), carbon steel, stainless steel and plastic (shock-free). Available in diameters ranging from 1-1/2" to 4" and lengths 48" to 54".

Morris Basic, Standard, Deluxe and Dissipator series of Gaylord Wands offer the user a variety of options including air adjusting, "stay" clip, handle and filtering screens.



## **Basic Model - Aluminum Construction**

Includes six air register holes and stand off loop at bottom.

Standard Length			Extended Length		
Diameter	Part No.	Length	Diameter	Part No.	Length
1-1/2	GBA 15U	48"	1-1/2	GBA 15UL	54"
2	GBA 20U	48"	2	GBA 20UL	54"
2-1/2	GBA 25U	48"	2-1/2	GBA 25UL	54"
3	GBA 30U	48"	3	GBA 30UL	54"
4	GBA 40U	48"	4	GBA 40UL	54"



## Standard Model - Aluminum Construction

Includes adjustable air register ring and stand off loop at bottom.

Standard Length			Extended Length		
Diameter	Part No.	Length	Diameter	Part No.	Length
1-1/2	GSA 15U	48"	1-1/2	GSA 15UL	54"
2	GSA 20U	48"	2	GSA 20UL	54"
2-1/2	GSA 25U	48"	2-1/2	GSA 25UL	54"
3	GSA 30U	48"	3	GSA 30UL	54"
4	GSA 40U	48"	4	GSA 40UL	54"



## **Deluxe Model - Aluminum Construction**

Includes adjustable air register ring, stand off loop, operator handle and Ever-Tite® cam and groove coupling.

Standard Length			Extended Length			
Diameter	Part No.	Length	Diameter	Part No.	Length	
1-1/2	GDA 15U	48"	1-1/2	GDA 15UL	54"	
2	GDA 20U	48"	2	GDA 20UL	54"	
2-1/2	GDA 25U	48"	2-1/2	GDA 25UL	54"	
3	GDA 30U	48"	3	GDA 30UL	54"	
4	GDA 40U	48"	4	GDA 40UL	54"	

Prices subject to change without notice.

©2021 Morris Coupling Company | Printed in U.S.A.