


MOULDPRO®

SAFETY COUPLINGS TYPE TS



The patented Mouldpro quick connect safety coupling features an automatic locking mechanism that offers an effective solution for accidental disconnection and unlocking.

The coupling is designed for use with aggressive media such as mould cooling applications with hot and cold water (as well as thermal oil) between -20°C (-4°F) and +200°C (+392°F)*.

High quality FKM o-rings mean that the coupling is ideal for mould cooling circuits especially for high temperature.


The couplings are available in both European and International series making it fully compatible with existing moulds; it is not necessary to change the connector nipples.

* water up to +180°C (+356°F) / oil up to +200°C (+392°F)

Coupling in unlocked position,
sleeve is in default position
ready to connect



Coupling in locked position, and green
code indicates that the coupling is
locked and safe




Purchase [Mouldpro Quick Connect Safety Couplings](https://www.plastixs.com/mouldpro-quick-connect-safety-couplings) online.

Contact sales@plastixs.com or call 888-792-2223 for sizes and styles that are not on our website, but available for purchase.

MOULDPRO

- 1 Strengthened release sleeve made of high-resistant special brass
- 2 Separate O-ring sealing on the connector
- 3 Special-Hitec-FKM-O-ring
- 4 Forced guidance design with visual color coding on the locking sleeve
- 5 Patented automatic safety locking mechanism (dependable security when disconnecting)



The Mouldpro quick connect safety coupling system is characterized by its simple and intuitive connection process.

Even in difficult and hidden areas, this enables a safe operation. The connection takes place via automatic locking.

An additional colour coding on the locking sleeve indicates a correct and secure connection clearly and unequivocally.

The disconnecting process can be blindly executed due to the forced guidance of the locking sleeve – it requires an axial movement of turning the locking sleeve, basically a manual unlocking motion.

An accidental or unintentional disconnection is practically impossible.

Purchase [Mouldpro Quick Connect Safety Couplings](#) online.

Contact sales@plastixs.com or call 888-792-2223 for sizes and styles that are not on our website, but available for purchase.




INTERNATIONAL SERIES

Purchase [Mouldpro Quick Connect Safety Couplings](#) online.

Contact sales@plastixs.com or call 888-792-2223 for sizes and styles that are not on our website, but available for purchase.

SAFETY COUPLING, TYPE TS, STRAIGHT




DN	Serie	Symbol	Symbol	A	D	L	L1
6	20	20K10V-TS	20K10-TS	10	18	59,5	22
9	30	30K10V-TS	30K10-TS	10	23	64,5	25
9	30	30K13V-TS	30K13-TS	13	23	64,5	25

SAFETY COUPLING, TYPE TS, 90°



DN	Serie	Symbol	Symbol	A	D	L	L1
6	20	20K10V/90-TS	20K10/90-TS	10	18	52,5	22
9	30	30K10V/90-TS	30K10/90-TS	10	23	68,5	25
9	30	30K13V/90-TS	30K13/90-TS	13	23	68,5	25

SAFETY COUPLING, TYPE TS, 45°



DN	Serie	Symbol	Symbol	A	D	L	L1
6	20	20K10V/45-TS	20K10/45-TS	10	18	52,5	22
9	30	30K10V/45-TS	30K10/45-TS	10	23	68,5	25
9	30	30K13V/45-TS	30K13/45-TS	13	23	68,5	25


MOULDPRO

INTERNATIONAL SERIES (continued)


Purchase [Mouldpro Quick Connect Safety Couplings](#) online.

Contact sales@plastixs.com or call 888-792-2223 for sizes and styles that are not on our website, but available for purchase.

SAFETY COUPLING, TYPE TS, MALE THREADED




(DN)	Serie	↺↻	↔	A	D	L	L1
6	20	20KUR1/4V-TS	20KUR1/4-TS	G1/4	18	55,5	11
6	20	20KUR3/8V-TS	20KUR3/8-TS	G3/8	18	55,5	11
9	30	30KUR1/4V-TS	30KUR1/4-TS	G1/4	23	57,5	12,5
9	30	30KUR3/8V-TS	30KUR3/8-TS	G3/8	23	57,5	12,5
9	30	30KUR1/2V-TS	30KUR1/2-TS	G1/2	23	57,5	12,5



MOULDPRO

EUROPEAN SERIES


SAFETY COUPLING, TYPE TS, STRAIGHT



(DN)	Serie	↺↻	↔	A	D	L	L1
6	9	09K10V-TS	09K10-TS	10	18	59,5	22
9	13	13K13V-TS	13K13-TS	13	23	63	25


MOULDPRO EUROPEAN SERIES (continued)

SAFETY COUPLING, TYPE TS, 90°




⌀	Serie	↻	↔	A	D	L	L1
6	9	09K10V/90-TS	09K10/90-TS	10	18	52,5	22
9	13	13K13V/90-TS	13K13/90-TS	13	23	68,5	25

SAFETY COUPLING, TYPE TS, 45°



⌀	Serie	↻	↔	A	D	L	L1
6	9	09K10V/45-TS	09K10/45-TS	10	18	52,5	22
9	13	13K13V/45-TS	13K13/45-TS	13	23	68,5	25


SAFETY COUPLING, TYPE TS, MALE THREADED



⌀	Serie	↻	↔	A	D	L	L1
6	9	09KUM14V-TS	09KUM14-TS	M14X1,5	18	55,5	11
6	9	09KUR1/4V-TS	09KUR1/4-TS	G1/4	18	55,5	11
6	9	09KUR3/8V-TS	09KUR3/8-TS	G3/8	18	55,5	11
9	13	13KUM16V-TS	13KUM16-TS	M16X1,5	23	57,5	12,5
9	13	13KUR1/4V-TS	13KUR1/4-TS	G1/4	23	57,5	12,5
9	13	13KUR3/8V-TS	13KUR3/8-TS	G3/8	23	57,5	12,5
9	13	13KUR1/2V-TS	13KUR1/2-TS	G1/2	23	57,5	12,5

Purchase [Mouldpro Quick Connect Safety Couplings](#) online.

Contact sales@plastixs.com or call 888-792-2223 for sizes and styles that are not on our website, but available for purchase.




MOULDPRO

SCANDINAVIAN SERIES

Purchase [Mouldpro Quick Connect Safety Couplings](#) online.


Contact sales@plastixs.com or call 888-792-2223 for sizes and styles that are not on our website, but available for purchase.

SAFETY COUPLING, TYPE TS, STRAIGHT




DN	Serie	Symbol	Symbol	A	D	L	L1
6	6	06K10V-TS	06K10-TS	10	18	59,5	22

SAFETY COUPLING, TYPE TS, 90°



DN	Serie	Symbol	Symbol	A	D	L	L1
6	6	06K10V/90-TS	06K10/90-TS	10	18	52,5	22

SAFETY COUPLING, TYPE TS, 45°



DN	Serie	Symbol	Symbol	A	D	L	L1
6	6	06K10V/45-TS	06K10/45-TS	10	18	52,5	22



MOULDPRO

SCANDINAVIAN SERIES (continued)


Purchase [Mouldpro Quick Connect Safety Couplings](#) online.

Contact sales@plastixs.com or call 888-792-2223 for sizes and styles that are not on our website, but available for purchase.

SAFETY COUPLING, TYPE TS, MALE THREADED



DN	Serie	↺	↔	A	D	L	L1
6	6	06KUR1/4V-TS	06KUR1/4-TS	G1/4	18	55,5	11
6	6	06KUR3/8V-TS	06KUR3/8-TS	G3/8	18	55,5	11



Purchase [Mouldpro Quick Connect Safety Couplings](#) online.

Contact sales@plastixs.com or call 888-792-2223 for sizes and styles that are not on our website, but available for purchase.