FDA Liquid Food Transfer AALFAGOMMA



T455LL 150 PSI Food Discharge Hose

3-A
COMPLIANT MATERIAL



Discharge of liquid, fatty, oily foods and alcoholic beverages, up to 150 proof or 75% alcohol content*. Hose may be sterilized with 5% soda solution.



Cover:

White NBR/PVC blend – abrasion, ozone and oil resistant.

Reinforcement:

High tensile textile cords.

Tube

White NBR. Meets FDA and 3A (18-03) requirements.



Working Pressure:

Constant Pressure - 10 Bar (150 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T455 10 BAR (150 PSI) – GENERAL PURPOSE FOOD TRANSFER (in black letters)

Standard Length:

100 feet

*This correction is to rectify the relationship between the unit proof and % alcohol content in the U.S. system. The alcohol content % = 0.5 x Proof. There are discrepancies between proof and % alcohol content as it differs from country to country. Calculations for the U.S. are shown here. EXAMPLE: Proof is a method of measuring the alcohol content of spirits. A spirits' product that has a 40% alcohol content by volume is 80 proof [40 multiplied by 2 = 80).

Nominal Specifications							
Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Standard Length (ft)	Weight (lbs./ft.)
T455LL150	1 1/2	38	1.89	48	150	100	0.60
T455LL200	2	51	2.48	63	150	100	0.95
T455LL300	3	76	3.46	88	150	100	1.38

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 36.

COUPLING SUGGESTIONS

Quick-Acting couplings attached with bands.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

