


 MADE IN THE
USA

TR1™ Series

Heavy-Duty, Rubber Blend Wet or Dry Material Handling Hose

GENERAL APPLICATIONS

- Fly ash collection
- Grain Handling
- Hydro excavation
- Industrial vacuum equipment
- Material handling – heavy duty abrasive
- Milling machine scrap recovery
- Rock, gravel, sand and crushed concrete vacuuming
- Sewer truck boom hose
- Shot blast recovery
- Slurry handling

CONSTRUCTION

Blended rubber tube with rigid PVC helix

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +150°F (+65°C)*

*Actual service temperature range is application dependent.

FEATURES AND ADVANTAGES

- **Superior Rubber Compounds** – Tigerflex™ uses specially engineered compounds which provide the ideal combination of excellent abrasion resistance, light weight, flexibility, static dissipation and superior long-lasting durability.
- **Static Dissipative Tube** - Specially formulated to help prevent the build-up of static electricity for added safety and to help keep material flowing smoothly.
- **“Cold-Flex” Materials** – Hose remains flexible in sub-zero temperatures.
- **Convoluted Cover Design** – Provides increased hose flexibility.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F			
TR1-150	1 1/2	38.5	1.94	49.2	35	26	Full	28	1.5	100	0.47
TR1-200	2	50.8	2.38	60.5	32	23	Full	26	1.5	100/50	0.65
TR1-250	2 1/2	63.4	3.05	77.5	30	22	Full	26	2.0	100/50	0.84
TR1-300	3	76.2	3.56	90.5	28	20	Full	26	2.5	100/50/20	0.90
TR1-400	4	101.6	4.67	118.5	26	18	Full	26	4.5	100/50/20	1.73
TR1-500	5	126.8	5.73	145.5	21	16	28	24	5.0	100/50/20	3.00
TR1-600	6	153.4	7.03	178.8	19	13	28	24	9.5	100/50/20	4.00
TR1-800	8	204.8	9.27	255.6	19	13	27	23	14	50/20	7.40

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.
- Available with grounding wire upon request. Minimum order required, contact Kuriyama customer service for details.

COMPLIANCES (for details see page 87)

RoHS (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.