



WOR™ Series

Standard-Duty, Oil Resistant, PVC Suction Hose

GENERAL APPLICATIONS

- Environmental clean-up
- Oil skimming
- Oil slurries
- Oil suction
- Vapor recovery – hydrocarbon emissions

CONSTRUCTION

Oil resistant PVC tube with rigid PVC helix

SERVICE TEMPERATURE RANGE

5°F (-15°C) to +150°F (+65°C)*

*Actual service temperature range is application dependent.



FEATURES AND ADVANTAGES

- Oil Resistant PVC – Made with special oil resistant compounds which exhibit medium resistance to oil and other hydrocarbons.
- Convoluted Outer Cover – Provides increased hose flexibility.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F			
WOR150	1 1/2	38.1	1.92	48.8	50	25	28	24	3	100	0.31
WOR200	2	50.8	2.40	61.0	40	20	28	24	4	100	0.50
WOR300	3	76.2	3.64	92.5	40	20	28	24	6	100	1.17
WOR400	4	101.6	4.72	119.9	35	18	28	22	10	100	1.74

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.
- Chemical Resistant Guides (for details see pages 108-109)

COMPLIANCES (for details see page 87)

Phthalate Free (10), RoHS (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.