

# JG-BLK™ Series

## Standard Duty PVC Suction Hose

### General Applications:

- Agricultural liquid fertilizer
- Air seeder lines
- Drain lines
- Irrigation lines
- Pumps, rental and construction dewatering
- Pumps, trash
- Water suction – standard duty

### Construction:

PVC tube with rigid PVC helix.

### Service Temperature:

-4°F (-20°C) to 150°F (+65°C)\*

### Features and Advantages:

- **Smooth Outer Cover** – Provides increased pressure rating and smooth surface for banding.
- **Phthalate Free.**



## Nominal Specifications

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating (in Hg)		Approx. Bending Radius (in @ 68°F)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F			
JG-BLK100	1	25.4	1.26	32.0	85	60	28	26	3	100	0.26
JG-BLK125	1-1/4	31.7	1.56	39.6	85	60	28	24	4	100	0.35
JG-BLK150	1-1/2	38.1	1.83	46.5	70	50	28	24	5	100	0.48
JG-BLK200	2	50.8	2.32	59.0	65	45	28	24	7	100	0.66
JG-BLK250	2-1/2	63.5	2.87	73.0	65	45	28	24	8	100	0.87

\*Actual service temperature range is application dependent.

### PHthalate FREE, RoHS

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

KTJGBLKFL1018