

Dual-Purpose Couplings For Tubing And Pipe



When higher pressures or applications requiring greater end-pull capabilities are encountered, these dual-flange couplings are recommended. Gasket is one piece with single row of interlocking teeth as illustrated. The outer shell with flanges and the inner sleeve are two pieces each. Dual-Purpose Couplings slide to position at the joint without removing the bolts ... or may be separated into halves for assembly around the joint.

Tubing or Nom. Pipe (IPS) Size	O.D. Tubing Pipe (A)	Morris Coupling Code	Coupling Length (B)	No. of Bolts	Size of Bolts	Weight Each (lbs.)	BLACK Neoprene Gasket*	FOOD-GRADE WHITE Neoprene Gasket*
							PIC No.	PIC No.
20**	20.000	20-5C-OD DP	12"	10	3/4 x 3	54.8	0820005B2	0820005W2
	20.000	20-6C-OD DP	16"	12	3/4 x 3	72.9	0820006B2	0820006W2
22**	22.000	22-5C-OD DP	12"	10	3/4 x 3	57.8	0822005B2	0822005W2
	22.000	22-6C-OD DP	16"	12	3/4 x 3	76.6	0822006B2	0822006W2
24**	24.000	24-5C-OD DP	12"	10	3/4 x 3	61.2	0824005B2	0824005W2
	24.000	24-6C-OD DP	16"	12	3/4 x 3	81.3	0824006B2	0824006W2
26**	26.000	26-5C-OD DP	12"	10	3/4 x 3	64.5	0826005B2	0826005W2
	26.000	26-6C-OD DP	16"	12	3/4 x 3	85.8	0826006B2	0826006W2
28**	28.000	28-5C-OD DP	12"	10	3/4 x 3	67.8	0828005B2	0828005W2
	28.000	28-6C-OD DP	16"	12	3/4 x 3	93.1	0828006B2	0828006W2

- WHEN ORDERING, always give the Code No. and O.D. of the pipe or tube on which coupling will be used.
- Dimensions of couplings to outside edges of flanges is coupling O.D. plus 5-1/2".
- **Tubing and pipe have same O.D. *Neoprene.