Plastixs • 151 Memorial Drive, Suite H • Shrewsbury • MA • 01545
888-792-2223 / 508-842-1606 • www.plastixs.com • sales@plastixs.com

Injection Molders Keep Their Cool with the Right High-Temperature Systems

If your molding operation is running hotter than ever, you're not alone. As more manufacturers work with advanced resins—especially in medical, electronics and automotive applications—mold temperatures continue to climb. Once you pass the 300°F threshold, the rules change and standard approaches no longer apply.

Suddenly, the equipment that worked fine for everyday molding becomes a liability. Traditional manifolds, hoses, and fittings simply aren't designed for the demands of high-temperature water or oil. That's why selecting the right equipment isn't just a matter of performance—it's a matter of safety, reliability and process stability.

Let's walk through what "the right equipment" means when you're dealing with high-temperature injection molding.

Traditional Manifolds Aren't Built for High Heat

Most standard manifolds—steel, aluminum, or basic stainless—are only rated for 250°F to 300°F. That's well below the temperatures required for many engineered materials.

Once you push beyond those limits, several problems appear quickly:

- Material softening (especially aluminum)
- Valve failure due to solder melting
- Loss of structural integrity
- Leaks caused by thermal expansion
- Safety hazards for operators working near the mold

If your process water is running at 320°F to 450°F, or your oil system is operating up to 600°F, you need equipment specifically engineered for those temperatures.

What a High-Temperature Manifold System Should Include

A proper high-temperature manifold assembly is more than a block of metal with ports. It's a complete system designed to handle extreme heat, pressure, and flow requirements.

Here are the key features to look for:

1. High-Temperature Ratings

A suitable manifold system should operate safely at:

- 320°F to 450°F for water
- Up to 600°F for oil
- Working pressures to as high as 680 PSI

Anything less is a risk.

2. Stainless Steel Construction

Stainless steel manifolds made from schedule 40 pipe offer:

- Superior corrosion resistance
- Structural stability at high temperatures
- Longer service life

Aluminum and standard square structural stainless steel simply don't hold up under sustained heat.

3. Leak-Free Connections

Look for:

- JIC fittings
- High-temperature quick connects
- Hydraulically crimped hose ends

These prevent leaks that can cause burns, slip hazards, or equipment damage.

4. Locking Shut-Off Valves

Locking handles prevent accidental opening—critical when dealing with superheated water or oil.

5. Insulated High-Temperature Hoses

Hoses should be:

- Stainless braided fluoropolymer or stainless steel
- Available with insulation sleeves to reduce heat loss and protect operators
- Rated for the same temperature and pressure as the manifold or more.

6. Flexible Configuration Options

Depending on your setup, you may need:

- 4 to 8 ports or more
- End-inlet or center-inlet designs
- Direct-mount or remote-mount options

The right configuration improves flow management and simplifies maintenance.

When Custom Manifolds Make Sense

Not every molding cell is the same. If your process has unique requirements—tight spaces, unusual port layouts or specialized flow needs—a custom manifold might be the best solution.

A well-designed custom assembly should offer:

- A "plug-and-play" installation
- Faster setups and teardowns
- Cleaner, safer hose routing
- Compatibility with high-temperature hoses and fittings
- A measurable improvement in uptime due to eliminating leaks

Custom doesn't just mean "different"—it means optimized.

Don't Forget the Supporting Components

A high-temperature manifold is only as good as the equipment connected to it. That includes:

- Insulated flexible hoses
- High-temperature hose assemblies

- Properly rated fittings and adapters

Every component in the loop must be able to withstand the same temperature and pressure. One weak link can compromise the entire system.

The Bottom Line

High-temperature injection molding demands equipment that's engineered for extreme conditions. The right manifold system:

- Improves safety
- Reduces leaks
- Maintains consistent flow
- Protects operators
- Extends equipment life
- Supports higher-performance materials

If your molding temperatures are rising, upgrading to the correct high-temperature manifold equipment isn't optional—it's essential.

Link to: Read the Plastixs whitepaper

Contact us to learn more about choosing the right equipment for your hitemp injection molding operations